

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

Smooth PVC installation pipe 750N with low friction





The Norwegian EPD Foundation

Owner of the declaration:

Pipelife Sverige AB

Product:

Smooth PVC installation pipe 750N with low friction

Declared unit:

1 kg

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR

NPCR Part A: Construction products and services

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-4416-3633-EN

Registration number:

NEPD-4416-3633-EN

Issue date:

02.05.2023

Valid to:

02.05.2028

EPD Software:

LCA.no EPD generator ID: 58768

General information

Product

Smooth PVC installation pipe 750N with low friction

Program operator:

Post Box 5250 Majorstuen, 0303 Oslo, Norway
The Norwegian EPD Foundation
Phone: +47 23 08 80 00
web: post@epd-norge.no

Declaration number:

NEPD-4416-3633-EN

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR Part A: Construction products and services

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 kg Smooth PVC installation pipe 750N with low friction

Declared unit (cradle to gate) with option:

A1-A3,A4,A5,C1,C2,C3,C4,D

Functional unit:

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Michael M. Jenssen, Asplan Viak AS
(no signature required)

Owner of the declaration:

Pipelife Sverige AB
Contact person:
Phone: +46 513 22114
e-mail: yvette.lennartsson@pipelife.com

Manufacturer:

Pipelife Sverige AB

Place of production:

Pipelife Sverige AB
Box 50
SE-524 02 Ljung , Sweden

Management system:

EN ISO 9001:2015 and EN ISO 14001:2015

Organisation no:

SE556087042901

Issue date:

02.05.2023

Valid to:

02.05.2028

Year of study:

2022

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804+A2 and seen in a construction context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Yvette Lennartsson

Reviewer of company-specific input data and EPD: Bjørn Svensson

Approved:

Håkon Hauan, CEO EPD-Norge

Product

Product description:

Smooth PVC installations pipes for Electro in house applications, with low friction inside layer.

Product specification

70005366, 70005367, 70005368, 70005369, 70005370, 70005371, 70005879, 70005880, 70005881, 70005883, 70008584, 70005885, 70005374, 70005375, 70005382, 70005383, 70005384, 70005385, 70005386, 70005387

Product related data to be found at Pipelife Sverige AB product catalogue <https://catalog.pipelife.com/se>

Materials	kg	%
Fire-, heat- and UV-stabilizers	0,02	2,42
Filler	0,09	8,64
Plastic	0,03	2,50
Polyvinyl chloride (PVC)	0,86	86,44
Total	1,00	

Technical data:

PVC material with density 580 kg/m³
 Produced according EN 61 386-1,-21
 Stiffness 750N

Market:

Europe, with scenario made for the Swedish market.

Reference service life, product

Lifetime on product calculated more than 100 years.

Reference service life, building

LCA: Calculation rules

Declared unit:

1 kg Smooth PVC installation pipe 750N with low friction

Cut-off criteria:

Allocation:

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.


Materials	Source	Data quality	Year
Filler	ecoinvent 3.6	Database	2019
Fire-, heat- and UV-stabilizers	ecoinvent 3.6	Database	2019
Plastic	ecoinvent 3.6	Database	2019
Polyvinyl chloride (PVC)	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X

System boundary:

EPD Process A1 – D VP PIPES



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

A5 = 5 % product losses during installation are estimated by the company. No energy use has been quantified since installation in buildings is often done by manual labour. Use of portable electrical devices (e.g., drill) usually have low energy requirements falling under the cut-off criterion of 1%.

C1 = de-construction in buildings is often done by manual labour. Use of portable electrical devices (e.g., drill) usually have low energy requirements falling under the cut-off criterion of 1%.

C3 and C4 = Waste treatment of the product follows the default values provided in EN 50693, Product Category Rules for life cycle assessments of electronic and electrical products and systems, table G.4. This table specified how different types of raw materials used in A1 will likely be treated during the end-of-life of the product. Waste treatments in C3 include material recycling and incineration with and without energy recovery and fly ash extraction. Disposal in C4 consist of landfilling of different waste fractions and of ashes.

D = The recyclability of metals and plastics allows the producers a credit for the net scrap that is produced at the end of a product's life. The benefits from recycling of net scrap are described in formula from EN 15804:2012+A2:2019. Substitution of heat and electricity generated by the incineration with energy recovery of plastics is also calculated in module D.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36,7 %	100	0,043	l/tkm	4,30
Assembly (A5)	Unit	Value			
Product loss during installation (percentage of cable pipe)	Units/DU	0,05			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36,7 %	100	0,043	l/tkm	4,30
Waste processing (C3)	Unit	Value			
Waste treatment of polyvinylchloride (PVC), incineration with energy recovery and fly ash extraction (kg)	kg	0,43			
Disposal (C4)	Unit	Value			
Landfilling of ashes from incineration of Polyvinylchloride (PVC), process per kg ashes and residues (kg)	kg	0,07			
Landfilling of plastic mixture (kg)	kg	0,43			
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of electricity (MJ)	MJ	0,44			
Substitution of thermal energy, district heating (MJ)	MJ	6,69			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO ₂ -eq	2,17E+00	1,63E-02	1,34E-01	0	1,63E-02	8,66E-01	6,57E-02	-4,02E-02
	GWP-fossil	kg CO ₂ -eq	2,16E+00	1,63E-02	1,33E-01	0	1,63E-02	8,66E-01	6,57E-02	-3,88E-02
	GWP-biogenic	kg CO ₂ -eq	8,75E-03	6,76E-06	4,99E-04	0	6,76E-06	3,53E-04	1,23E-05	-8,01E-05
	GWP-luluc	kg CO ₂ -eq	3,32E-03	5,81E-06	1,84E-04	0	5,81E-06	6,76E-05	2,96E-06	-1,34E-03
	ODP	kg CFC11 -eq	1,06E-06	3,70E-09	5,31E-08	0	3,70E-09	2,85E-08	2,40E-09	-2,83E-03
	AP	mol H ⁺ -eq	9,91E-03	4,69E-05	6,38E-04	0	4,69E-05	5,01E-04	7,86E-05	-3,19E-04
	EP-FreshWater	kg P -eq	9,19E-05	1,31E-07	4,86E-06	0	1,31E-07	2,55E-06	2,77E-07	-3,45E-06
	EP-Marine	kg N -eq	1,75E-03	9,29E-06	1,18E-04	0	9,29E-06	1,22E-04	7,63E-05	-1,04E-04
	EP-Terrestrial	mol N -eq	1,87E-02	1,04E-04	1,29E-03	0	1,04E-04	1,31E-03	2,84E-04	-1,13E-03
	POCP	kg NMVOC -eq	6,56E-03	3,98E-05	4,22E-04	0	3,98E-05	3,71E-04	8,89E-05	-3,12E-04
	ADP-minerals&metals ¹	kg Sb -eq	4,93E-05	4,51E-07	2,80E-06	0	4,51E-07	1,82E-06	8,40E-08	-3,86E-07
	ADP-fossil ¹	MJ	5,49E+01	2,47E-01	2,87E+00	0	2,47E-01	1,14E+00	2,00E-01	-5,55E-01
	WDP ¹	m ³	5,05E+02	2,39E-01	1,99E+01	0	2,39E-01	2,33E+01	2,55E+00	-6,91E+00

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption







"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 PM	Disease incidence	7,70E-08	1,00E-09	5,57E-09	0	1,00E-09	3,26E-09	1,09E-09	-1,94E-08
 IRP ²	kgBq U235 -eq	2,25E-01	1,08E-03	9,74E-03	0	1,08E-03	5,54E-03	1,02E-03	-3,54E-03
 ETP-fw ¹	CTUe	3,30E+01	1,83E-01	2,44E+00	0	1,83E-01	5,46E+01	4,04E-01	-3,02E+00
 HTP-c ¹	CTUh	1,46E-09	0,00E+00	8,30E-11	0	0,00E+00	1,21E-10	1,80E-11	-5,50E-11
 HTP-nc ¹	CTUh	4,03E-08	2,00E-10	1,97E-09	0	2,00E-10	1,29E-08	6,43E-10	-2,89E-09
 SQP ¹	dimensionless	8,15E+00	1,73E-01	4,42E-01	0	1,73E-01	4,15E-01	7,04E-01	-3,71E+00


PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator




2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	3,96E+00	3,54E-03	1,77E-01	0	3,54E-03	1,45E-01	1,36E-02	-3,43E+00
	PERM	MJ	0,00E+00	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	PERT	MJ	3,96E+00	3,54E-03	1,77E-01	0	3,54E-03	1,45E-01	1,36E-02	-3,43E+00
	PENRE	MJ	3,47E+01	2,47E-01	1,86E+00	0	2,47E-01	1,14E+00	2,00E-01	-5,55E-01
	PENRM	MJ	2,05E+01	0,00E+00	1,02E+00	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	PENRT	MJ	5,51E+01	2,47E-01	2,89E+00	0	2,47E-01	1,14E+00	2,00E-01	-5,55E-01
	SM	kg	1,49E-02	0,00E+00	7,57E-04	0	0,00E+00	0,00E+00	4,75E-05	0,00E+00
	RSF	MJ	1,65E-01	1,26E-04	3,32E-03	0	1,26E-04	2,63E-03	3,17E-04	-6,00E-04
	NRSF	MJ	5,07E-02	4,52E-04	2,17E-03	0	4,52E-04	0,00E+00	1,63E-03	-2,03E-01
	FW	m ³	2,43E-01	2,64E-05	1,21E-02	0	2,64E-05	2,73E-02	2,17E-04	-4,13E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

*Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"






*INA Indicator Not Assessed

End of life - Waste										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 HWD	kg	5,72E-03	1,27E-05	5,27E-04	0	1,27E-05	0,00E+00	6,21E-03	-2,61E-05	
 NHWD	kg	2,75E-01	1,20E-02	1,84E-02	0	1,20E-02	0,00E+00	4,95E-01	-1,31E-02	
 RWD	kg	1,54E-04	1,68E-06	6,39E-06	0	1,68E-06	0,00E+00	8,89E-07	-2,90E-06	

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

End of life - Output flow										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 CRU	kg	0,00E+00	0,00E+00	0,00E+00	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00	
 MFR	kg	6,38E-03	0,00E+00	3,19E-04	0	0,00E+00	0,00E+00	3,88E-05	0,00E+00	
 MER	kg	1,32E-02	0,00E+00	6,60E-04	0	0,00E+00	4,32E-01	9,48E-07	0,00E+00	
 EEE	MJ	7,91E-03	0,00E+00	3,95E-04	0	0,00E+00	4,42E-01	6,15E-05	0,00E+00	
 EET	MJ	1,20E-01	0,00E+00	5,98E-03	0	0,00E+00	6,69E+00	9,31E-04	0,00E+00	

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0,00E+00
Biogenic carbon content in accompanying packaging	kg C	0,00E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Electricity, Sweden (kWh)	ecoinvent 3.6	54,94	g CO ₂ -eq/kWh

Dangerous substances

No substances given by the REACH Candidate list or the Norwegian priority list are intentionally added to the product.

Indoor environment





Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products									
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	2,09E+00	1,63E-02	1,30E-01	0	1,63E-02	8,69E-01	1,71E-02	-3,96E-02

GWPI-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
 ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
 EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
 ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
 ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
 Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no rapportnummer: : 07.21.
 Vold, et al., (2019) EPD generator for Pipelife - Background information for customer application and LCA data. report number 08.19
 NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.

	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 23 08 80 00 e-mail: post@epd-norge.no web: www.epd-norge.no
	Owner of the declaration: Pipelife Sverige AB Box 50 , SE-524 02 Ljung	Phone: +46 513 22114 e-mail: yvette.lennartsson@pipelife.com web:
	Author of the Life Cycle Assessment LCA.no AS Dokka 6B, 1671	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6B,1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal