

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

PE Optimal Cable Protection Pipes in coil



PIPELIFE 

Owner of the declaration:
Pipelife Sverige AB

Product:
PE Optimal Cable Protection Pipes in coil

Declared unit:
kg

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR Part A: Construction products and services. Ver. 2.0 March 2021

Program operator:
EPD-Global

Declaration number:
NEPD-12810-14103

Issue date:
29.10.2025

Valid to:
29.10.2030

EPD software:
LCAno EPD generator ID: 1269355

EPD-Global

General information

Product

PE Optimal Cable Protection Pipes in coil

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Declaration number:

NEPD-12810-14103

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR Part A: Construction products and services. Ver. 2.0 March 2021

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

kg PE Optimal Cable Protection Pipes in coil

Declared unit (cradle to gate) with option:

A1-A3, A4, A5, C1, C2, C3, C4, D

Functional unit:

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Michael M. Jenssen, Asplan Viak AS

(no signature required)

Owner of the declaration:

Pipelife Sverige AB
Contact person:
Phone: +46 513 22114
e-mail: yvette.lennartsson@pipelife.com

Manufacturer:

Pipelife Sverige AB

Place of production:

Pipelife Sverige AB
Box 50
SE-524 02 Ljung , Sweden

Management system:

EN ISO 9001:2015 and EN ISO 14001:2015

Organisation no:

SE556087042901

Issue date:

29.10.2025

Valid to:

29.10.2030

Year of study:

2024

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804+A2 and seen in a construction context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global.

Developer of EPD: Yvette Lennartsson

Reviewer of company-specific input data and EPD: Bjørn Svensson

Approved:



Håkon Hauan, CEO EPD-Global

Product

Product description:

Smooth PE cable protection pipes in coil.
Products are UV stable.
Classified as SRS or SRE-P.

Product specification

Product related data to be found at Pipelife Sverige AB product catalogue <https://catalog.pipelife.com/se>.

Materials	kg	%
Pigments	0.005	0.50
Plastic - Polyethylene (HDPE)	0.99	99.00
Polyethylene (HDPE)	0.005	0.50
Total	1.00	100.00

Technical data:

PE material with density 960 kg/m³.
Produced partly with re-cycled material.
Produced according Verksnorm 5200.

Market:

Europe, with scenario made for the Swedish market.

Reference service life, product

Lifetime on product calculated more than 100 years.

Reference service life, building

LCA: Calculation rules

Declared unit:

kg PE Optimal Cable Protection Pipes in coil

Cut-off criteria:

Allocation:

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.


Materials	Source	Data quality	Year
Pigments	ecoinvent 3.6	Database	2019
Plastic - Polyethylene (HDPE)	ecoinvent 3.6	Database	2019
Polyethylene (HDPE)	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use		De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7		C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND		X	X	X	X	X

System boundary:

EPD process A1-D PE OPTIMAL Cable Protection pipes



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

A5 = 5 % product losses during installation are estimated by the company. According to NPCR 028, other activities such as excavating/backfilling trenches and other additional materials are not included, these are expected to be included at construction level assessments.

C1 = According to NPCR 028, other activities such as excavating/backfilling trenches and other additional materials are not included, these are expected to be included at construction level assessments. This module can therefore be included with zero impact.

C3 - C4 = Waste treatment of the product follows the default values provided in EN 50693, Product Category Rules for life cycle assessments of electronic and electrical products and systems, table G.4. This table specified how different types of raw materials used in A1 will likely be treated during the end-of-life of the product. Waste treatments in C3 include material recycling and incineration with and without energy recovery and fly ash extraction. Disposal in C4 consist of landfilling of different waste fractions and of ashes.

D = The recyclability of metals and plastics allows the producers a credit for the net scrap that is produced at the end of a product's life. The benefits from recycling of net scrap are described in formula from EN 15804:2012+A2:2019. Substitution of heat and electricity generated by the incineration with energy recovery of plastics is also calculated in module D.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 6 (km)	53.3 %	100.00	0.023	l/tkm	2.30
Assembly (A5)					
Assembly (A5)	Unit	Value			
Product loss during installation (percentage of cable pipe)	Units/DU	0.05			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36.7 %	100.00	0.043	l/tkm	4.30
Waste processing (C3)					
Waste processing (C3)	Unit	Value			
Waste treatment of polyethylene (PE), incineration with energy recovery and fly ash extraction (kg)	kg	0.4975			
Landfilling of ashes from incineration of Polyethylene (PE), process per kg ashes and residues (kg)	kg	0.495			
Waste treatment of plastic mixture, incineration with energy recovery and fly ash extraction (kg)	kg	0.0025			
Disposal (C4)					
Disposal (C4)	Unit	Value			
Landfilling of plastic mixture (kg)	kg	0.005			
Landfilling of ashes from incineration of Polyethylene (PE), process per kg ashes and residues (kg)	kg	0.01753			
Landfilling of ashes from incineration of Plastic mixture, process per kg ashes and residues (kg)	kg	0.00008742			
Benefits and loads beyond the system boundaries (D)					
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of electricity (MJ)	MJ	0.9686			
Substitution of thermal energy, district heating (MJ)	MJ	14.65			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO ₂ -eq	6.97E-01	8.72E-03	1.13E-01	0	1.63E-02	1.53E+00	1.55E-03	-8.81E-02
	GWP-fossil	kg CO ₂ -eq	6.94E-01	8.71E-03	1.13E-01	0	1.63E-02	1.53E+00	1.55E-03	-8.50E-02
	GWP-biogenic	kg CO ₂ -eq	3.01E-03	3.73E-06	1.53E-04	0	6.76E-06	2.68E-05	5.65E-07	-1.75E-04
	GWP-luluc	kg CO ₂ -eq	4.61E-04	2.65E-06	2.38E-05	0	5.81E-06	5.95E-06	1.58E-07	-2.93E-03
	ODP	kg CFC11 -eq	4.84E-08	2.10E-09	2.92E-09	0	3.70E-09	4.02E-09	1.18E-10	-6.19E-03
	AP	mol H ⁺ -eq	2.00E-03	2.80E-05	1.18E-04	0	4.69E-05	2.84E-04	3.76E-06	-7.00E-04
	EP-FreshWater	kg P -eq	2.23E-05	6.93E-08	1.15E-06	0	1.31E-07	4.90E-07	1.38E-08	-7.55E-06
	EP-Marine	kg N -eq	5.06E-04	6.14E-06	3.22E-05	0	9.29E-06	1.20E-04	1.78E-06	-2.29E-04
	EP-Terrestrial	mol N -eq	5.13E-03	6.85E-05	3.32E-04	0	1.04E-04	1.32E-03	1.35E-05	-2.47E-03
	POCP	kg NMVOC -eq	1.52E-03	2.69E-05	9.57E-05	0	3.98E-05	3.28E-04	3.84E-06	-6.82E-04
	ADP-minerals&metals ¹	kg Sb-eq	9.35E-06	1.55E-07	5.08E-07	0	4.51E-07	2.01E-07	5.63E-09	-8.45E-07
	ADP-fossil ¹	MJ	2.01E+01	1.41E-01	1.04E+00	0	2.47E-01	3.42E-01	9.77E-03	-1.21E+00
	WDP ¹	m ³	5.78E+02	1.08E-01	2.91E+01	0	2.39E-01	2.85E+00	1.03E-01	-1.51E+01

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

The products are produced on 100% renewable energy according mass balance principle.

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 PM	Disease incidence	2.75E-08	8.00E-10	1.56E-09	0	1.00E-09	1.90E-09	4.90E-11	-4.24E-08
 IRP ²	kgBq U235 -eq	1.04E+00	6.18E-04	5.19E-02	0	1.08E-03	1.33E-03	4.68E-05	-7.76E-03
 ETP-fw ¹	CTUe	8.15E+00	1.03E-01	4.61E-01	0	1.83E-01	7.68E-01	1.78E-02	-6.61E+00
 HTP-c ¹	CTUh	4.98E-10	0.00E+00	2.80E-11	0	0.00E+00	5.60E-11	1.00E-12	-1.21E-10
 HTP-nc ¹	CTUh	1.00E-08	1.00E-10	6.24E-10	0	2.00E-10	2.13E-09	3.00E-11	-6.33E-09
 SQP ¹	dimensionless	3.13E+00	1.62E-01	2.09E-01	0	1.73E-01	6.80E-01	2.80E-02	-8.12E+00

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	2.88E+00	1.78E-03	1.45E-01	0	3.54E-03	1.76E-02	5.73E-04	-7.50E+00
	PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PERT	MJ	2.88E+00	1.78E-03	1.45E-01	0	3.54E-03	1.76E-02	5.73E-04	-7.50E+00
	PENRE	MJ	-2.21E+01	1.41E-01	-1.07E+00	0	2.47E-01	3.42E-01	9.77E-03	-1.21E+00
	PENRM	MJ	4.23E+01	0.00E+00	2.11E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PENRT	MJ	2.02E+01	1.41E-01	1.05E+00	0	2.47E-01	3.42E-01	9.77E-03	-1.21E+00
	SM	kg	9.90E-01	0.00E+00	4.95E-02	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	6.33E-02	6.23E-05	3.20E-03	0	1.26E-04	4.47E-04	1.40E-05	-1.31E-03
	NRSF	MJ	1.78E-02	2.09E-04	3.53E-03	0	4.52E-04	5.04E-02	1.79E-03	-4.45E-01
	FW	m ³	9.55E-02	1.61E-05	4.80E-03	0	2.64E-05	5.08E-04	9.36E-06	-9.04E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = $9.0 \cdot 10^{-3}$ = 0.009"

End of life - Waste										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 HWD	kg	2.51E-02	7.74E-06	2.29E-02	0	1.27E-05	4.19E-01	1.48E-02	-5.71E-05	
 NHWD	kg	1.23E-01	1.23E-02	1.96E-02	0	1.20E-02	2.30E-01	1.32E-02	-2.87E-02	
 RWD	kg	2.55E-04	9.66E-07	1.30E-05	0	1.68E-06	1.47E-06	5.95E-08	-6.36E-06	

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

End of life - Output flow										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 CRU	kg	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 MFR	kg	0.00E+00	0.00E+00	2.24E-08	0	0.00E+00	0.00E+00	4.48E-07	0.00E+00	
 MER	kg	1.99E-02	0.00E+00	2.60E-02	0	0.00E+00	5.00E-01	1.10E-08	0.00E+00	
 EEE	MJ	1.18E-02	0.00E+00	4.90E-02	0	0.00E+00	9.69E-01	7.12E-07	0.00E+00	
 EET	MJ	1.79E-01	0.00E+00	7.42E-01	0	0.00E+00	1.47E+01	1.08E-05	0.00E+00	

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	0.00E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, Nuclear, based on Guarantee of Origin from Ecohz AS, 2024 (kWh)	ecoinvent 3.10.1	7.88	g CO ₂ -eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products									
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	6.96E-01	8.72E-03	1.13E-01	0	1.63E-02	1.54E+00	1.59E-03	-8.68E-02

GWPIOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
 ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
 EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
 ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
 ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
 Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no rapportnummer: : 07.21.
 Vold, et al., (2019) EPD generator for Pipelife - Background information for customer application and LCA data. report number 08.19
 NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.

 epd-global Powered by EPD-Norway	Program operator and publisher EPD-Global Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-global.com
	Owner of the declaration: Pipelife Sverige AB Box 50 , SE-524 02 Ljung , Sweden	Phone: +46 513 22114 e-mail: yvette.lennartsson@pipelife.com web:
	Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Sweden	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal