






Art	E-nr	Färg	RAL
541GR	7701402	GRAFIT	7016
541W	7701401	VIT	9003

Allmän information

Typ armatur	Vägg/takarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Opal polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul AC
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	1,41kg / 1,93kg
Förpackning mått [cm]	30,5x30,5x11
LED	Lumens DLM 90C 10W xxx 230V / A V0.1 (Produktblad)
Led modul effekt	10W
Armatur effekt	10W
Lumen modul	1100lm
Lumen ut	403lm
Led modul effekt	110lm/W
Armaturens effekt	40,3lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	A+
Effektfaktor	PF > 0,97
THD-faktor	< 20%
Ta nominell:	+25°C
Maximal omgivningstemperatur	-30...+25°C
Inrush current	150mA/500µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer