



## Allmän information

Typ armatur	Väggarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Polykarbonat med optisk struktur, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Bakkantsdimmer
Netto / Bruttovikt armatur	1,34kg / 1,47kg
Förpackning mått [cm]	24x12x9,5
LED	Philips Strip 0.5ft 490lm 8xx FC HV5 (Produktblad)
Drivdon	Philips Xitanium 7W 0,35A 20V TE SC 230V (Produktblad)
Led modul effekt	4W
Armatur effekt	5,4W
Lumen modul	681lm
Lumen ut	444lm
Armaturens effekt	82,2lm/W
ULOR	0%
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>70 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	<b>A++</b>
Effektfaktor	PF > 0,9
THD-faktor	< 20%
Ta nominel:	+25°C
Inrush current	1A / 15,2µs

## Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit, BIM ArchiCAD

