


Art	E-nr	Färg	RAL
1742AL	7704579	ALUMINIUM	9006
1742GR	7704580	GRAFIT	7016
1742B	7705585	SVART	9005
1742W	7704581	VIT	9003

Allmän information

Typ armatur	Väggarmatur
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Glas - härdad, klart
Typ ljuskälla	LED modul AC
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	1,1kg / 1,16kg
LED	Lumens EDC 38C 8W xxx 230V A101 3K (☞ Produktblad)
Led modul effekt	8W
Armatur effekt	8W
Lumen modul	756lm
Lumen ut	563lm
Led modul effekt	94,5lm/W
Armaturens effekt	70,4lm/W
ULOR	0%
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	 / ☞ EPREL
Effektfaktor	PF>0,98
THD-faktor	< 20%
Ta nominel:	+25°C
Maximal omgivningstemperatur	-35...+25°C
Inrush current	35mA / 60ms

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

