



Art	E-nr	Färg	RAL
1482GA	7747377	GALVANISERAT STÅL	-
1482B	7747378	SVART	9005

Allmän information

Typ armatur	
Material	Galvaniserad stål
Diffuser/Avskärmning:	PMMA, opal
Typ ljuskälla	LED modul AC
Ljusstyrning	Dimbar (Triac)
Netto / Bruttovikt armatur	13,35kg / 14,25kg
LED	Lumens EDC 47C 10W xxx 230V A Ver.1.2 (Produktblad)
Led modul effekt	10W
Armatur effekt	10,5W
Lumen modul	1098lm
Lumen ut	295lm
Led modul effekt	109,8lm/W
Armaturens effekt	28,1lm/W
ULOR	44%
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	A++
Effektfaktor	0,98
THD-faktor	< 20%
Ta nominel:	+25°C
Maximal omgivningstemperatur	-35...+25°C
Inrush current	43mA / 60ms

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer