



Art	E-nr	Färg	RAL
1247AL	7747379	ALUMINIUM	9006
1247GR	7747380	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Bakkantsdimmer
Netto / Bruttovikt armatur	4,84kg / 5,64kg
Förpackning mått [cm]	22,5x22,5x37
LED	Cree XP-G3 DK1305003-VA05 (Produktblad)
Drivdon	Philips Xitanium 7W 0,35A 20V TE SC 230V (Produktblad)
Led modul effekt	6,6W
Armatur effekt	8,4W
Lumen modul	854lm
Lumen ut	312lm
Led modul effekt	129,4lm/W
Armaturens effekt	37,1lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>145 000h
LED-fotobiologiskt hot	RG0 or RG1
Effektfaktor	PF 0,98
THD-faktor	< 20%
Ta nominel:	+25°C
Maximal omgivningstemperatur	+45°C
Inrush current	1A/15,2µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

