



Art	E-nr	Färg	RAL
1240AL	7747385	ALUMINIUM	9006
1240GR	7747386	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Bakkantsdimmer
Netto / Bruttovikt armatur	11,03kg / 12,69kg
Förpackning mått [cm]	22,5x22,5x103,5
LED	Cree XP-G3 DK1305003-VA05 (Produktblad)
Drivdon	Philips Xitanium 10W 0,5A 20V TE SC 230V (Produktblad)
Led modul effekt	9.6W
Armatur effekt	12.2W
Lumen modul	1179lm
Lumen ut	428lm
Led modul effekt	122,8lm/W
Armaturens effekt	35,1lm/W
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>145 000h
LED-fotobiologiskt hot	RG0 or RG1
Effektfaktor	PF 0,98
THD-faktor	< 20%
Ta nominel:	+25°C
Maximal omgivningstemperatur	+45°C
Inrush current	3,36A/36µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

