



Art	E-nr	Färg	RAL
557AL	7747391	ALUMINIUM	9006
557GR	7747392	GRAFIT	7016

Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Netto / Bruttovikt armatur	10,84kg / 13,16kg
Förpackning mått [cm]	31,5x29x99
LED	Philips Fortimo SLM C 1208 L15 2024 G7 (Produktblad)
Drivdon	Philips Xitanium 36W/m 929001486006 (Produktblad)
Led modul effekt	19W
Armatur effekt	21,8W
Lumen modul	3137lm
Lumen ut	556lm
Led modul effekt	165,1lm/W
Armaturens effekt	25,5lm/W
ULOR	0%
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
Energieffektivitetsindex (EEI)	A++
THD-faktor	20%
Ta nominel:	+25°C
Inrush current	4,6A / 65µs
Antal armaturer på automatsäkring	B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

