



Art	E-nr	Färg	RAL
777AL	7747617	ALUMINIUM	9006
777GR	7747618	GRAFIT	7016

Allmän information

Typ armatur	Stolpe
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Glas - härdad, klart
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Netto / Bruttovikt armatur	9,18kg / 11,75kg
Förpackning mått [cm]	80x62x62
LED	Philips SLM C 830 1211 L19 2828 G7
Drivdon	Philips Xitanium 36W/m 929001486006 (Produktblad)
Led modul effekt	33,9W
Armatur effekt	36,4W
Lumen modul	5127lm
Lumen ut	3190lm
Led modul effekt	151,2lm/W
Armaturens effekt	87,6lm/W
ULOR	6,84%
Färgtemperatur	3000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
Energieffektivitetsindex (EEI)	A++
Effektfaktor	PF 0,97
Ta nominel:	+25°C
Maximal omgivningstemperatur	+35°C
Inrush current	4,6A / 65µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer, BIM Revit, BIM ArchiCAD