



Allmän information

| | |
|-----------------------------------|-------------------------------------|
| Typ armatur | Pollare |
| Material | Pulverlackerad aluminium |
| Diffuser/Avskärmning: | Klart polykarbonat, UV stabiliserat |
| Typ ljuskälla | LED modul + driver |
| Ljusstyrning | Bakkantsdimmer |
| Netto / Bruttovikt armatur | 11,03kg / 12,69kg |
| Förpackning mått [cm] | 22,5x22,5x103,5 |
| LED | 1305003G2 Cree XD16 4000K |
| Drivdon | Philips Xitanium 10W 0,5A 20V TE SC |
| Led modul effekt | 9,6W |
| Armaturs effekt | 12,2W |
| Lumen modul | 1171lm |
| Lumen ut | 493lm |
| Led modul effekt | 122lm/W |
| Armaturens effekt | 40,4lm/W |
| Färgtemperatur | 4000K |
| Färgbeständighet (McAdam ellipse) | SDCM3 |
| Färgtolkningsindex (CRI/Ra) | 80 |
| Nominell livstid L70/B50 vid 25°C | 50 000h |
| Effektfaktor | PF > 0,98 |
| Ta nominel: | +25°C |
| Inrush current | 3,36A / 36µs |

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

