




Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul + driver
Ljusstyrning	Ej dimbar
Netto / Bruttovikt armatur	10,84kg / 13,16kg
Förpackning mått [cm]	31,5x29x99
LED	Philips Fortimo SLM C 1208 L15 2024 G7 (Produktblad)
Drivdon	Philips Xitanium 36W/m 929001486006 (Produktblad)
Led modul effekt	19,2W
Armatur effekt	21,8W
Lumen modul	3264lm
Lumen ut	564lm
Led modul effekt	170lm/W
Armaturens effekt	25,9lm/W
ULOR	0%
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
Energieffektivitetsindex (EEL)	A++
Ta nominel:	+25°C
Inrush current	4,6A / 65µs
Antal armaturer på automatsäkring	B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer

