



Allmän information

Typ armatur	Pollare
Material	Pulverlackerad aluminium
Diffuser/Avskärmning:	Klart polykarbonat, UV stabiliserat
Typ ljuskälla	LED modul + driver
Netto / Bruttovikt armatur	10,84kg / 13,6kg
Förpackning mått [cm]	31,5x29x99
LED	Philips Fortimo SLM C 1208 L15 2024 G7 (Produktblad)
Drivdon	Osram OT 40/170-240/1A0 4DIML2 NFC E (Produktblad)
Drivdon hållbarhet	100000h
Külsó ellenőrzés	DALI2 (4DIM) (Användarhandbok)
Led modul effekt	19W
Armatur effekt	21,8W
Lumen modul	3264lm
Lumen ut	582lm
Led modul effekt	171,8lm/W
Armaturens effekt	26,7lm/W
ULOR	0%
Färgtemperatur	4000K
Färgbeständighet (McAdam ellipse)	SDCM3
Färgtolkningsindex (CRI/Ra)	80
Nominell livstid L70/B50 vid 25°C	>50 000h
LED-fotobiologiskt hot	RG0 or RG1
Energieffektivitetsindex (EEI)	A++
Effektfaktor	PF 0,99
THD-faktor	< 10 %
Spänning	6 / 10kV
Ta nominel:	+25°C
Inrush current	26A / 180µs

Filer som kan laddas ned

Photometric LDT files, Photometric IES files, Manualer