



**5.7W** 5.7W

Coastal protected

**IP65** IP65 ideal for outdoor environments

## WL075

Silver straight to mains, high output LED wall light

### Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.2kg
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

### Guarantee

Warranty 7 years

### Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Straight to mains wall light, perfect for framing entrances and illuminating columns
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL075SNBM27	Silver	5.7W	2700K	110°	515	90	2763	
WL075SNBM30	Silver	5.7W	3000K	110°	520	91	2789	
WL075SNBM40	Silver	5.7W	4000K	110°	530	93	2843	
WL075BNBM27	Black	5.7W	2700K	110°	515	90	2763	
WL075BNBM30	Black	5.7W	3000K	110°	520	91	2789	
WL075BNBM40	Black	5.7W	4000K	110°	530	93	2843	
WL075ZNBM27	Bronze	5.7W	2700K	110°	515	90	2763	
WL075ZNBM30	Bronze	5.7W	3000K	110°	520	91	2789	

### Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

### Accessories

N/A	No accessories required
-----	-------------------------

Beam angle: **110°**

