



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

# WL075

Silver straight to mains, high output LED wall light

## Features

IP Rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

## Installation information

UK Bathroom Zone	2
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
Weight	1.2kg
Ambient Temperature Range	40°C
SELV	SELV
Electric Class (1, 2, 3)	1

## Guarantee

7 years

## Features & benefits

- 5.7W
- Coastal protected
- IP65 ideal for outdoor environments
- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Straight to mains wall light, perfect for framing entrances and illuminating columns
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs

## Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL075SNBM27	Silver	5.7W	2700K	110°	515	90	2763
WL075SNBM30	Silver	5.7W	3000K	110°	520	91	2789
WL075SNBM40	Silver	5.7W	4000K	110°	530	93	2843
WL075BNBM27	Black	5.7W	2700K	110°	515	90	2763
WL075BNBM30	Black	5.7W	3000K	110°	520	91	2789
WL075BNBM40	Black	5.7W	4000K	110°	530	93	2843
WL075ZNBM27	Bronze	5.7W	2700K	110°	515	90	2763
WL075ZNBM30	Bronze	5.7W	3000K	110°	520	91	2789

## Wiring information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

## LED driver

N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A
------------------------------	----------	-----	----	---	-----	-----

## Accessories

N/A	No accessories required
-----	-------------------------

Light source energy efficiency:

Beam angle: 110°

