



1W

1W at 350mA or 2W at 700mA

Frosted effect for low glare and soft lighting

Low voltage ground light

GL016 Frosted

1W, 15lm ground marker light

Features		Installation Information	
IP rating	IP68	Input	350mA / 700mA
CSP Switchable	Single CCT	Maximum Ambient Temperature	50°C
LED Lifetime	L70 70,000h	Weight	400g
Colour Rendering Index	CRI>80	Inrush Current	N/A
Colour Consistency	SDCM3	Cut Out Size	50
IK rating	IK09	Construction Material	Stainless steel (316)
Walk Over / Drive Over	Walk over	UK Bathroom Zone	0
		SELV	SELV
		Electric Class (1, 2, 3)	3
		Earth Leakage	N/A
		Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	lx @ 1m	W	Energy
				350mA				700mA	
GL016DC0F40	Stainless steel	4000K	100°	1W	15	15	5	2W	
GL016DC0F30	Stainless steel	3000K	100°	1W	13	13	5	2W	
GL016DC0F27	Stainless steel	2700K	100°	1W	12	12	4	2W	
GL016BC0F27	Black	2700K	100°	1W	12	12	4	2W	
GL016BC0F30	Black	3000K	100°	1W	13	13	5	2W	
GL016BC0F40	Black	4000K	100°	1W	15	15	5	2W	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/50	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

Guarantee

Warranty 7 years

Features & benefits

- Robust cable for outdoor use
- Shallow depth for easy installation
- Marine-grade stainless steel 316 or Black anodised aluminium

