



GL100

Up to 2W, 14lm mini domed stainless steel marker light

Features

IP rating	IP68
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
IK rating	IK07
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	215g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316) or brass
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Type	Colour	Beam	W	lm	lm/W	W	lm	lm/W	Energy
					350mA			700mA			
GL100DX3X30	Stainless steel 316	3 Windows	3000K	75°	1W	6	6	2W	12	6	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE
Output Cable Type	N/A

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP700I8W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



collingwood



1W at 350mA or 2W at 700mA



Coastal protected

Low voltage ground light

Guarantee

Warranty 7 years

Features & benefits

- Walk over ground light ideal for paths or steps
- Marine grade stainless steel 316 or antique brass
- IP68 rated
- Long-lifetime of 70,000hrs
- 7-year warranty

Beam angle: 75°

