



GL040

Up to 4.6W, 530lm ground light

Features

IP rating	IP68
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
IK rating	IK08
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	720g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	Ix @ 1m	W	lm	lm/W	Ix @ 1m	Energy
				350mA				700mA				
GL040DWBX27	Stainless steel 316	2700K	40°	2.2W	290	290	562	4.6W	515	515	998	
GL040DWBX30	Stainless steel 316	3000K	40°	2.2W	290	132	581	4.6W	520	112	1008	
GL040DWBX40	Stainless steel 316	4000K	40°	2.2W	300	141	600	4.6W	530	115	1027	
GL040DNBX27	Stainless steel 316	2700K	12°	2.2W	310	132	3096	4.6W	515	112	5499	
GL040DNBX30	Stainless steel 316	3000K	12°	2.2W	290	136	3203	4.6W	520	113	5552	
GL040DNBX40	Stainless steel 316	4000K	12°	2.2W	300	141	3310	4.6W	530	115	5659	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	4
PLU/700 3-9	220-240V	Yes	No	0	1	4
PSIP70018W	220-240V	Yes	No	0	1	3

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
GLA01	Square transformer plate	Sold Separately



2.2W at 350mA or 4.6W at 700mA

Coastal protected

Low voltage ground light

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316
- Long lifetime of 70,000hrs

