Ground lights specification sheet



collingwood



Straight to mains ground light

GL200

5.7W, 40Im, domed ground light

Features

IP rating	IP65
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
IK rating	IK10
Walk Over / Drive Over	Walk over

Installation Information			
Input	220-240V AC		
Maximum Ambient Temperature	35°C		
Weight	960g		
Inrush Current	31A 0.12ms		
Cut Out Size	70		
Construction Material	Stainless steel (316)		
UK Bathroom Zone	2		
SELV	SELV		
Electric Class (1, 2, 3)	1		
Earth Leakage	0.1mA		
Suitable for coastal areas	Yes		

2 window 1 directio

2 windows 2 direction

Photometrics @ 25°C

Product Code	Finish	Туре	w	Colour	Beam	lm	lm/W	Energy
GL200DX1X30	Stainless steel 316	1 Window	5.7W	3000K	90°	10	2	A E

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	No	2	-	-

Accessories


JB5	Gell filled waterproof connector	Sold Separately
TUBE/68	Installation tube	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

Guarantee Warranty

7 years

Features & benefits

- Marine grade stainless steel 316 or antique brass
- 5 window styles and colour temperatures to suit any installation
- Drive over suitable for use on driveways (with TUBE/68)





in collingwoodlighting