



# GL050

3W, 50lm marker ground light

## Features

IP rating	IP68
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
IK rating	IK08
Walk Over / Drive Over	Walk over

## Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	552g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Earth Leakage	N/A
Suitable for coastal areas	Yes

## Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL050 NW	Stainless steel	3W	4000K	100°	50	17	20	
GL050 WW	Stainless steel	3W	3000K	100°	46	15	16	
GL050 27	Stainless steel	3W	2700K	100°	46	15	16	

## Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

## LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	3
PSIP3509W	220-240V	Yes	No	0	1	2
PSMD35039	220-240V	Yes	Yes (mains)	0	1	3

## Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



3W at 350mA



Frosted effect for low glare and soft lighting

Low voltage ground light


## Guarantee

Warranty 7 years

## Features & benefits

- Robust cable for outdoor use
- Brushed steel finish for sleek effect

Beam angle: 100°



Ø76mm

