

Uplights (Façade lights) specification sheet



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Volta 1000mm

Wall washing light bar

Features

IP Rating	IP65
CSP Switchable	Single CCT
Dimmable Option	Yes (Mains)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

UK Bathroom Zone	1
Inrush Current	15A 10s
Construction Material	Anodised aluminium
Weight	2.5kg
Ambient Temperature Range	50°C
SELV	Yes
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
LL1000MT30	Silver	40W	3000K	30°	4200	105	10745
LL1000WT30	Silver	40W	3000K	60°	4200	105	4251
LL1000AT30	Silver	40W	3000K	20x35°	4200	105	10860
LL1000MT27	Silver	40W	2700K	30°	4200	105	10745
LL1000WT27	Silver	40W	2700K	60°	4200	105	4251
LL1000AT27	Silver	40W	2700K	20x35°	4200	105	10860

Wiring information

Cable / Flying Lead	0.8m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED driver

N/A (integrated SELV driver)	220-240V	Yes	N/A	N/A	N/A	N/A
------------------------------	----------	-----	-----	-----	-----	-----

Accessories

N/A	No accessories required
-----	-------------------------

Guarantee

7 years

Features & benefits

- 40W
- IP65 ideal for outdoor environments
- Suitable for use in coastal applications
- Plug and play through-wire install method
- Supplied with waterproof connectors for fast install
- 3000K and 2700K range with choice of 2000 or 4200 lumen output
- Narrow beam 30°, Wide beam 60° or Asymmetrical 20x35°
- Also available in 500mm

Light source energy efficiency:



Beam angle: 30°, 60°, 20x35°

