



Tilt RGBW ground light

Driverless, RGBW Colour Change

Features

IK Rating	IK10
IP Rating	IP67
CSP Switchable	RGBW
Tiltable	25°
Walk Over / Drive Over	Drive over (15mph maximum)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation information

Cut Out Size	119
UK Bathroom Zone	2
Construction Material	Anodised aluminium body, 316 SS bezel
Weight	GLTM_11: 0.99kg, GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg ,GLTM_22: 3.98kg
Ambient Temperature Range	-25°C - 40°C
Electric Class (1, 2, 3)	3

Wiring information

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 5x1.0mm2
Type of Wiring Required	Series

LED drivers

CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	N/A	4
CCDRV75DMX	220-240V	Yes	Yes	2	N/A	4
CCDRV75RF	220-240V	Yes	Yes	2	N/A	4

Accessories

JB5	Gel filled waterproof junction box	Sold Separately
-----	------------------------------------	-----------------

PRODUCT CODES

	Colour / Finish	Description	Characteristic 1	Characteristic 2
GLTXS119RGBW	Stainless steel 316	Tilt XGround 119mm, 40°, RGBW-3000K	119mm cut-out	IK08
GLTXS147RGBW	Stainless steel 316	Tilt XGround 147mm, 40°, RGBW-3000K	147mm cut-out	IK08
GLTXS165RGBW	Stainless steel 316	Tilt XGround 165mm, 40°, RGBW-3000K	165mm cut-out	IK10
GLTXS193RGBW	Stainless steel 316	Tilt XGround 193mm, 40°, RGBW-3000K	193mm cut-out	IK10
GLTXS223RGBW	Stainless steel 316	Tilt XGround 223mm, 40°, RGBW-3000K	223mm cut-out	IK10



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 years

Features & benefits

- RGBW
- IP67 for complete protection against ingress of dust & water
- IK10 for protection against high impact
- Suitable for coastal applications
- Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees
- Static loading capacity is 2000kg
- Pre-wired with 1 meter of cable to aid the installer
- TRIAC mains dimmable and DALI-2 dimmable options also available

Light source energy efficiency:



Beam angle: 40°

