



EUROPE'S
LEADER IN
SIGNALLING


EvoSIGNAL Quick Finder.
Simply clever!



Find the right product
from the
EvoSIGNAL series

EvoSIGNAL offers a complete
product range with a
significantly reduced
number of variants.
Simply clever!

EvoSIGNAL
MINI



LIGHT EFFECTS
TwinLIGHT*, TwinFLASH*

APPLICATION RANGE

For installation in locations with **limited** space; for indoor and outdoor applications.

TYPICAL APPLICATIONS

Building services engineering; for small machines and devices.

Optical

12 V		24 V		115/230 V	
TwinLIGHT	TwinFLASH	TwinLIGHT	TwinFLASH	TwinLIGHT	TwinFLASH
Order no.	Order no.	Order no.	Order no.	Order no.	Order no.
260 110 74	260 120 74	260 110 75	260 120 75	260 110 60	260 120 60
260 210 74	260 220 74	260 210 75	260 220 75	260 210 60	260 220 60
260 310 74	260 320 74	260 310 75	260 320 75	260 310 60	260 320 60
260 410 74	260 420 74	260 410 75	260 420 75	260 410 60	260 420 60
260 510 74	260 520 74	260 510 75	260 520 75	260 510 60	260 520 60

TriCOLOUR
260 430 75

+ Mounting adapter compulsory!

Optical-audible

12 V		24 V		115/230 V	
TwinLIGHT	TwinFLASH	TwinLIGHT	TwinFLASH	TwinLIGHT	TwinFLASH
Order no.	Order no.	Order no.	Order no.	Order no.	Order no.
460 110 74	460 120 74	460 110 75	460 120 75	460 110 60	460 120 60
460 210 74	460 220 74	460 210 75	460 220 75	460 210 60	460 220 60
460 310 74	460 320 74	460 310 75	460 320 75	460 310 60	460 320 60
460 410 74	460 420 74	460 410 75	460 420 75	460 410 60	460 420 60
460 510 74	460 520 74	460 510 75	460 520 75	460 510 60	460 520 60

+ Mounting adapter compulsory!

max. 95 dB

Audible

12 V	24 V	115/230 V
Order no. 160 700 74	Order no. 160 700 75	Order no. 160 700 60

+ Mounting adapter compulsory!

max. 95 dB

Mounting adapter

Base mounting
Order no. 260 700 01

Installation mounting M22
Order no. 260 700 03

Installation mounting PG 29
Order no. 260 700 04

Tube mounting
Order no. 260 700 05

Bracket mounting with cable gland
Order no. 260 700 06

Bracket mounting
Order no. 260 700 07

EvoSIGNAL
MIDI



LIGHT EFFECTS
TwinLIGHT*, TwinFLASH*, Rotating Light

APPLICATION RANGE

Flexible **medium-range** signalling solutions; for indoor and outdoor applications.

TYPICAL APPLICATIONS

Building services engineering, door and gate applications, machinery and plant equipment systems.

Optical

12/24 V			115/230 V		
TwinLIGHT	TwinFLASH	Rotating	TwinLIGHT	TwinFLASH	Rotating
Order no.	Order no.	Order no.	Order no.	Order no.	Order no.
261 110 70	261 120 70	261 140 70	261 110 60	261 120 60	261 140 60
261 210 70	261 220 70	261 240 70	261 210 60	261 220 60	261 240 60
261 310 70	261 320 70	261 340 70	261 310 60	261 320 60	261 340 60
261 410 70	261 420 70	261 440 70	261 410 60	261 420 60	261 440 60
261 510 70	261 520 70	261 540 70	261 510 60	261 520 60	261 540 60

TriCOLOUR
261 430 70

+ Mounting adapter compulsory!

Optical-audible

12/24 V		115/230 V	
TwinLIGHT	TwinFLASH	TwinLIGHT	TwinFLASH
Order no.	Order no.	Order no.	Order no.
461 110 70	461 120 70	461 110 60	461 120 60
461 210 70	461 220 70	461 210 60	461 220 60
461 310 70	461 320 70	461 310 60	461 320 60
461 410 70	461 420 70	461 410 60	461 420 60
461 510 70	461 520 70	461 510 60	461 520 60

+ Mounting adapter compulsory!

max. 110 dB

Audible

12/24 V	115/230 V
Order no. 161 700 70	Order no. 161 700 60

+ Mounting adapter compulsory!

max. 110 dB

Mounting adapter

Base mounting
Order no. 261 700 01

Base mounting with Cable gland
Order no. 261 700 02

Tube mounting
Order no. 261 700 05

Bracket mounting with cable gland
Order no. 261 700 06

Bracket mounting
Order no. 261 700 07

Horn
Order no. 261 700 03

EvoSIGNAL
MAXI



LIGHT EFFECTS
TwinLIGHT*, TwinFLASH*, Rotating Light

APPLICATION RANGE

Flexible **long-range** signalling solutions; for indoor and outdoor applications.

TYPICAL APPLICATIONS

Building services engineering, door and gate applications, long-range solutions for machinery and plant equipment systems.

Optical

12/24 V			115/230 V		
TwinLIGHT	TwinFLASH	Rotating	TwinLIGHT	TwinFLASH	Rotating
Order no.	Order no.	Order no.	Order no.	Order no.	Order no.
262 110 70	262 120 70	262 140 70	262 110 60	262 120 60	262 140 60
262 210 70	262 220 70	262 240 70	262 210 60	262 220 60	262 240 60
262 310 70	262 320 70	262 340 70	262 310 60	262 320 60	262 340 60
262 410 70	262 420 70	262 440 70	262 410 60	262 420 60	262 440 60
262 510 70	262 520 70	262 540 70	262 510 60	262 520 60	262 540 60

+ Mounting adapter compulsory!

Mounting adapter

Base mounting
Order no. 262 700 01

Base mounting for cable exit at side
Order no. 262 700 02

Bracket mounting with cable gland
Order no. 262 700 06

Bracket with concealed cable entry
Order no. 262 700 07

AVAILABLE COLOURS



LIGHT EFFECTS

*TwinLIGHT and TwinFLASH two light effects in one element - also suitable for use as a signal escalation.

TwinLIGHT: Permanent Light and Blinking Light
TwinFLASH: Flashing Light and EVS Light

The light effects and our configurator can be found at www.werma.com.

WERMA Signaltechnik GmbH + Co. KG

Dürbheimer Str. 15
D-78604 Rietheim-Weilheim
Phone +49 74 24 95 57-0
Fax +49 74 24 95 57-44
www.werma.com
info@werma.com

WERMA Signaltechnik

Niederlassung Neuhausen am Rhf.
Rheingoldstrasse 50
8212 Neuhausen am Rheinfall
Switzerland
Phone +41 52 674 0060
Fax +41 52 674 0066
www.werma.ch
info@werma.ch

WERMA Italia S.r.l.

Via dell'Artigianato 42
29122 Piacenza
Italy
Phone +39 05 23 04 45 44
www.werma.it
info@werma.it

WERMA SARL

56, Rue Colière
69780 Mions
France
Phone +33 472 22 37 37
Fax +33 472 22 37 64
www.werma.fr
info@werma.fr

WERMA BENELUX

Poortakkerstraat 41C
9051 Sint-Denijs-Westrem
Belgium
Phone +32 9 220 31 11
www.wermabenelux.com
info@wermabenelux.com

WERMA (UK) Ltd.

11 Regent Park
37 Booth Drive
Park Farm Industrial Estate
Wellingborough NN8 6GR
Great Britain
Phone +44 1536 48 69 30
Fax +44 1536 51 48 10
www.werma.co.uk
uksales@werma.co.uk

WERMA USA Inc.

6731 Collamer Road
East Syracuse, NY 13057 USA
Phone +1 315 414 0200
Fax +1 315 414 0201
www.werma.com
us-info@werma.com

WERMA (Shanghai) Co., Ltd.

No. 8, High Technology Zone,
No. 503, Meinengda Road,
Songjiang, Shanghai, P. R. C
201613
China
Phone +86 21 57 74-0022
Fax +86 21 57 74-6601
www.werma.com.cn
info@werma.com.cn



11/18 · 540.000.007 · E