

Technical specifications See Item no. list Ratings Rated voltage 230 V AC (1-phase, 50-60Hz) Mode 2 Charging type Plug for connection to grid from socket See table Connection to vehicle Type 2 C RCD 30 mA AC & 6mA DC GRID type Seamless TN & IT grid Overheat protection In ICCB & domestic plug -40°C to +50°C Operating temperature [°C] -50°C to +85°C Storage temperature [°C] Size ICCB (L x W x T) 310 x 85 x 55 mm Aluminium with double protected plastic end caps Material control box (ICCB) IP 44 IP rating vehicle plug IP rating control box (ICCB) IP 67 Weight 2,1 kg Certification CE, IEC 61851, IEC 62752, IEC 62196 Recycling EE-waste

eMove EV portable charger

Item no: 502003

eMove EV portable charger

Mode 2 I Type 2

eMove Mode 2 is a portable charger for electric vehicles that has been made with the user in mind. Unique features, unmatched user-friendliness and extreme durability for safe charging on the move.

Efficient cable management: Cable clips and guides keep the cable tidy and convenient to bring with you.

Robust and durable: Aluminum housing ensures a long product life, even in rough conditions

Easy to wind: The markets most flexible cable, even in temperatures down to -40°C

Flexible mounting options: Use wall bracket included with the product or hang from hook

Safe power connection: It checks temperature in domestic plug and control box and charging

will stop if temperature becomes too high

User-friendly: Intuitive interface

Power Adjustment: User can reduce charging current to protect the infrastructure where the cable is connected

High mode: High mode provides faster charging for the first 120 minutes (see table)

eMove - made with the user in mind.

Item no.*	Normal	High rating for	Pre-set low	Total	Domestic plug	IP rating
	rating [A]	120 min [A]	rating [A]	length[m]	(with protective earth)	plug
502003	10	15	8	6	CEE 7/7 Type E / Type F	IP44

^{*} Check national regulations or defa.com for max current allowed for your country.