



Easee

Charge Pro

The Easee Charge Pro is a smart EV charger built to power large-scale charging networks. It features a MID-certified meter to enable professional services like public billing, reimbursement, and fleet management.

With remote monitoring and maintenance via Easee Control, plus continuous over the air software updates and V2G-ready hardware, the Charge Pro is built to perform today and stay ahead of tomorrow.

Features

- MID Class B accuracy, according to EN 50470-3.
- Easee Link™ Local Load & Phase balancing.
- Automatic queuing system.
- Permanent locking of the Type 2 cable.
- Integrated RFID reader (NFC / ISO 14443 and MIFARE Classic®).
- Universal, fits all types of electric cars & power supplies.
- Full control with the Easee App or third-party integrations.
- Manufacturer warranty: 5 years in accordance with Easee's warranty procedure.
- Conforms to functionality of ISO 15118-2 and designed to support ISO 15118-20.
- Compatible with OCPP 1.6J (Proxy) + OCPP 1.6J Direct.
- Designed to support future OCPP 2.X standard

Safety

Protection

Integrated RCD type A 30 mA AC according to EN 60947-2.
Integrated RDC-DD 6mA DC complying with IEC 62955, 9.9.
Temperature monitoring.
Overload protection.
Degree of protection: IP54 (the backplate is IP22 without cover).
Impact resistance: IK10.
Overvoltage category III.
Theft protection.
Read more at easee.com/manuals

Complies with the following regulations

2014/53/EU (RED).
2011/65/EU (RoHS).
2014/30/EU (EMCD).
2014/35/EU (LVD).
MID 2014/32/EU.
The Electric Vehicles (Smart Charge Points) Regulations 2021.
See DoC for details at easee.support

Technical

Charging power

1-phase: 1.4 kW (6 A) - 7.4 kW (32 A).
3-phase TN: 4.1 kW (6 A) - 22 kW (32 A).
3-phase IT: 2.4 kW (6 A) - 12.7 kW (32 A).

Electrical

Voltage: 3x 230 V / 400 V AC (+/-10%).
Grid frequency: 50 Hz.
Power grid: TN, IT, TT.
Connection point: Type-2 socket (Mode 3).
Automatic adjustment of charging speed based on available current.
Automatic charging with solar generation.¹
Automatic phase balancing.
Built-in energy meter MID Class B (±1 %).
V2G-ready

Connectivity

Wi-Fi 2.4 GHz b/g/n.
Bluetooth BLE 4.2.
Built-in 4G LTE E-sim (Cat M1) connectivity.
OCPP 1.6J (Cloud) and OCPP 1.6J Direct
Easee LinkRF (Local communication between chargers and to the Equalizer).
Built-in RFID/NFC reader for access control.
Easee App & Easee Control for control and monitoring.

General

Dimension (mm): H: 256 x W: 193 x D: 106.
Wall mounting (mm): c/c H: 160 x W: 125.
Operating temperature: -30 °C to +40 °C.
Weight: 1.6 kg.

Easee App

Reliable user friendly control

Get powerful local control of your charger by connecting via Bluetooth or via the cloud and get access to many useful features

- Control charging.
- View charger status.
- Lock/unlock charging cable.
- Authorize charging with app.
- Charging session summary.
- Lifetime consumption counter.
- Available energy overview.
- Configuration.

The information in this document is for information purposes only, is provided as is, and may be subject to change without notice. Easee ASA, including its subsidiaries, does not accept any liability for the correctness or completeness of the information and illustrations, and is not liable or responsible for your considerations, assessments, decisions or absence of such, or other use of the information in this document.

No part of this publication may be re-published, reproduced, transmitted or re-used in any other form, by any means or in any form, for your own or any third-party's use, unless otherwise agreed with Easee or its subsidiaries in writing. Any permitted use shall always be done in accordance with good practice and ensure that no harm may be caused to Easee or by misleading the consumer.

Easee and Easee products, product names, trademarks and slogans, whether registered or not, are Easee's intellectual property and may not be used without Easee's prior written permission. All other products and services mentioned may be trademarks or service marks of their respective owners.

The latest version of this publication can be downloaded at <http://easee.support>

July 2025 - Version 1.01

© 2025 by Easee ASA. All rights reserved.



Easee ASA
Vassbotnen 23
4033 Stavanger, Norway
Org.nr: 920 292 046

Easee is distributed and maintained by a network of qualified partners and resellers. Find more information and your local partner at:

www.easee.com