

Order No.: 5XA779121V00EA | **GTIN (EAN):** 4058352974049

Product description: FL11mxproRe,ECG-unit,Powd740,DA,1500W



Floodlight FL 11 maxi pro Remote ECG unit; colour temperature: 4000K, colour rendering: CRI > 70, light colour: 740; brightness control: DALI (with two DALI addresses); with terminal, 8-pole, max. 2.5mm², mains connection: 220..240V/380..400V AC, surge voltage resistance: line to ground: 10kV, dimming range 10..100%, LED unit replaceable on mast without ESD environment, LED unit replaceable, dustproof LED module, LED unit replaceable without ESD environment, no afterglow with DALI off / DMX off command, ECG replaceable separately; 1500W ECG unit ECG unit of diecast aluminium, uncoated natural; length: 500mm / width: 152mm / height: 77mm; equipment: Power double, protection rating (complete): IP66; insulation class (complete): insulation class I (protective earthing); certification: CE, ENEC, VDE; permissible operating ambient temperature: -40..+30°C, permissible storage temperature: -40..+85°C packaging unit: 1 piece



Wt. (kg): 5.6
GTIN (EAN): 4058352974049

Order No.: 5XA779121V00EA | GTIN (EAN): 4058352974049

Detailed technical description: FL11mxproRe,ECG-unit,Powd740,DA,1500W



Key data

- Product type: ECG unit
- Product name: Floodlight FL 11 maxi pro Remote
- Order No.: 5XA779121V00EA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740
- Rated input power: 1500W

Operating device:

- Control: DALI (2 addresses)

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -40..+30°C
- Certification, designation: CE, ENEC, VDE

Material, Colour

- ECG unit: diecast aluminium, uncoated, natural
- Colour specification: natural

Electrical connection

- Connection: terminal, 8-pole, max. 2.5mm²
- Nominal voltage: 220..240V/380..400V, AC
- Surge voltage resistance: line to ground: 10kV

Dimensions, Weight

- Length: 500mm
- Width: 152mm
- Height: 77mm
- Weight: 5.6kg