

## UK\_DS\_9916



### Blown Fibre Push-Fit Connectors



### Product Description

Details of the common push-fit straight connector, end cap, size-change connector. In sizes to match the microduct (m/d) diameters, the fittings are pushed onto a clean-cut m/d end and make a seal with internal O-rings. If the m/d is pulled away from the connector, internal teeth and a tapered body cause the tube to be gripped tighter. Removal of the m/d is achieved by pressing the collet inwards. Emtelle manuals explain more on connector features and use.

### Material

- BODY:** acetal copolymer, impact resistant.  
some are transparent.
- COLLET:** acetal copolymer, stainless steel teeth
- O-RINGS:** nitrile rubber
- Connector Range (all mm dimensions unless otherwise stated)



(photos of typical connectors are shown)

Straight Connectors Tube OD/ID	Code
3mm	9916
4mm	9917
5/3.5mm	9918
5/2.1mm	7823
6mm	7310
6.3mm (1/4")	7930
7/5.5mm	9919
7/3.5mm	70193
8/6mm	9920
8/3.5mm	9772
10/8mm	9921
12/10mm	9922
14/10mm	9923
14/12mm	9821
16/12 or 16/13	9924

End Caps	Code
3mm	9932
4mm	9933
5mm	9934
6mm	9975
7mm	9935
8mm	9936
10mm	9937
12mm	
14mm	9939
16mm	70153

Reducer Connectors	Code
5 - 3	9925
5/2.1 - 3/2.1	9926
5 - 4	71650
6 - 4	70294
6.3 - 5 (3/16")	9502
7 - 3	70407
7 - 4	70764
7 - 4 (3.5 bore)	72059
7 - 5	70031
8/3.5 - 3	70117
8 - 5	9927
8 - 6	73776
8 - 7	72024
10 - 5	70032
10 - 6	71048
10 - 7	70033
10 - 8	9928
12 - 5	70034
12 - 7	9929
12 - 10	9930
14 - 7	75592
14 - 10	70035
14 - 12	9931
16 - 10	75544
16 - 12	70036
18 - 16	75529

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

[www.emtelle.com](http://www.emtelle.com)

## UK\_DS\_9916

### Performance

---

<b>Blowing Pressure:</b>	Between temperatures of -10°C and +40°C, all listed connector sizes can be used for blowing operations at pressures up to 16bar. Between +40°C and +65°C, blowing pressures for 10mm and larger should not exceed 10bar.	
<b>Gas Tightness</b>	Leakage at 8 bar gas pressure:	1ml/minute approx.
	Leakage at 0.7 bar gas pressure:	0.01ml/minute approx.
<b>Water Ingress:</b>	The connectors shall seal against a 6m head of water.	
<b>Insertion force:</b>	50N max (5kg)	
<b>Retention force:</b>	25N min (3mm m/d)	125N min (8mm m/d)
(collet not held in)	55N min (5mm m/d)	125N min (10mm m/d)

Product Code	Description
71051	Locking Clip 7/8mm (x100)
71350	Rubber Stop 3.5/0.8 Split (x500)

### End of Specification

This document is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle Group [2020]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.

[www.emtelle.com](http://www.emtelle.com)