VIZULO

COLIBRI Eco

CLE 020 730 L22 AA008 CJK NG1



Artikelnummer: 7729670

Vizulo artikelnr: 83103255


CE RoHS

Color RAL 7035


Electrical	**Input power**	20 W
	Input voltage	220 - 240 V
	Frequency	50 - 60 Hz
	Power factor	0.93
Optical	**Optic name**	L22
	Distribution type	TYPE-III
	Longitudinal classification	M
	Luminous flux	2451 lm ±7%
	Luminous efficacy	123 lm/W
	Performance temperature Tq	+25 °C
	Constant light output	No
	Color rendering index	>70
	Color temperature	3000 K
	Color tolerance	5 SDCM
	ULOR	0
	LED quantity	8
Lifetime	**Lumen depreciation**	L90 after 100 000 h
	Warranty	8 years
	Ambient temperature range	-40 ... +50 °C
Protection	**Protection class**	Class I
	Surge protection L-N	6 kV
	Surge protection L/N-PE	10 kV
	LED module thermal protection w/ NTC	No

	Max products per MCB B16	33
	Max products per MCB C16	55
	Ingress protection	IP66
	Impact resistance	IK08
Housing	**Body material**	Die-cast aluminium
	Cover material	Flat tempered glass
	Optic material	PMMA
	Color	RAL 7035 (light grey)
	Dimensions	449 x 165 x 81 mm
	Max wind load area SCd	0.03 m²
	Mounting	Side-entry, 42, 48, 60 / post top, 60 mm
	LED module replaceability	Replaceable by a professional
	Driver replaceability	Replaceable by a professional
	Accessibility of electronic components	With tools
Controls	**Dimming**	No dimming
Approvals	**CE**	Yes
	RoHS	Yes

Light distribution



Dimensions



Product images







