VIZULO

MINI MARTIN Flood Smooth Tool-less Eco

MRSFSTE 075 740 L08 AA024 CJF NG2



Artikelnummer: 7760740

Vizulo artikelnr: 55111735

CE RoHS

Color RAL 7035

Electrical	**Input power**	75 W
	Input voltage	220 - 240 V
	Frequency	50 - 60 Hz
	Power factor	0.99
	Inrush current	30.25 A / 266 µs
Optical	**Optic name**	L08
	Distribution type	TYPE-II
	Longitudinal classification	VS
	Luminous flux	11179 lm ±7%
	Luminous efficacy	149 lm/W
	Performance temperature Tq	+25 °C
	Constant light output	No
	Color rendering index	>70
	Color temperature	4000 K
	Color tolerance	5 SDCM
	ULOR	0
	LED quantity	24
Lifetime	**Lumen depreciation**	L90 after 100 000 h
	Warranty	8 years
	Ambient temperature range	-40 ... +50 °C
Protection	**Protection class**	Class II
	Surge protection L-N	6 kV

	Surge protection L/N-PE	10 kV
	LED module thermal protection w/ NTC	No
	Max products per MCB B16	17
	Max products per MCB C16	28
	Ingress protection	IP66
	Impact resistance	IK08

Housing

	Body material	Die-cast aluminium
	Cover material	Flat tempered glass
	Optic material	PMMA
	Color	RAL 7035 (light grey)
	Dimensions	466 x 257 x 60 mm
	Max wind load area SCd	0.04 m²
	Mounting	Flood light
	LED module replaceability	Replaceable by a professional
	Driver replaceability	Replaceable by a professional
	Accessibility of electronic components	Tool-less


Controls

	Dimming	No dimming


Approvals

	CE	Yes
	RoHS	Yes

Light distribution



Dimensions



Product images







