MINI MARTIN Flood Smooth Tool-less Eco

MRSFSTE 075 740 L35 AA024 CJF NG2



Artikelnummer: 7760741


Vizulo artikelnr: 55111734

CE RoHS


Color		RAL 7035
Electrical	**Input power**	75 W
	Input voltage	220 - 240 V
	Frequency	50 - 60 Hz
	Power factor	0.99
	Inrush current	30.25 A / 266 µs
Optical	**Optic name**	L35
	Distribution type	TYPE-IV
	Longitudinal classification	M
	Luminous flux	10094 lm ±7%
	Luminous efficacy	135 lm/W
	Performance temperature Tq	+25 °C
	Constant light output	No
	Color rendering index	>70
	Color temperature	4000 K
	Color tolerance	5 SDCM
	ULOR	0
	LED quantity	24
Lifetime	**Lumen depreciation**	L90 after 100 000 h
	Warranty	8 years
	Ambient temperature range	-40 ... +50 °C

Protection	**Protection class**	Class II
	Surge protection L-N	6 kV
	Surge protection L/N-PE	10 kV
	LED module thermal protection w/ NTC	No
	Max products per MCB B16	17
	Max products per MCB C16	28
	Ingress protection	IP66
	Impact resistance	IK08
Housing	**Body material**	Die-cast aluminium
	Cover material	Flat tempered glass
	Optic material	PMMA
	Color	RAL 7035 (light grey)
	Dimensions	466 x 257 x 60 mm
	Max wind load area SCd	0.04 m²
	Mounting	Flood light
	LED module replaceability	Replaceable by a professional
	Driver replaceability	Replaceable by a professional
	Accessibility of electronic components	Tool-less
Controls	**Dimming**	No dimming
Approvals	**CE**	Yes
	RoHS	Yes

Light distribution



Dimensions



Product images

