VIZULO

OWL Eco
OWE 300 740 L08 AB160 CJF NG2



**Artikelnummer:** 7760746
**Vizulo artikelnr:** 47103003

CE RoHS

Color RAL 7035

| | | |
|---|---|---|
| Electrical | **Input power** | 300 W |
| | **Input voltage** | 220 - 240 V |
| | **Frequency** | 50 - 60 Hz |
| | **Power factor** | 0.98 |
| | **Inrush current** | 160 A / 225 µs |
| | **Stand-by power** | 0.32 W |
| Optical | **Optic name** | L08 |
| | **Distribution type** | TYPE-II |
| | **Longitudinal classification** | VS |
| | **Luminous flux** | 49524 lm ±7% |
| | **Luminous efficacy** | 165 lm/W |
| | **Performance temperature Tq** | +25 °C |
| | **Constant light output** | No |
| | **Color rendering index** | >70 |
| | **Color temperature** | 4000 K |
| | **Color tolerance** | 5 SDCM |
| | **ULOR** | 0 |
| | **LED quantity** | 160 |
| Lifetime | **Lumen depreciation** | L90 after 100 000 h |
| | **Driver failure rate** | <10% in 100 000 h |
| | **Warranty** | 10 years |
| | **Ambient temperature range** | -40 ... +50 °C |
| Protection | **Protection class** | Class II |


| | | |
|---|---|---|
| | **Surge protection L-N** | 6 kV |
| | **Surge protection L/N-PE** | 10 kV |
| | **LED module thermal protection w/ NTC** | No |
| | **Max products per MCB B16** | 4 |
| | **Max products per MCB C16** | 6 |
| | **Ingress protection** | IP66 |
| | **Impact resistance** | IK08 |

| | | |
|---|---|---|
| Housing | **Body material** | Die-cast aluminium |
| | **Cover material** | Flat tempered glass |
| | **Optic material** | PMMA |
| | **Color** | RAL 7035 (light grey) |
| | **Dimensions** | 533 x 655 x 85 mm |
| | **Mounting** | Standard |
| | **LED module replaceability** | Replaceable by a professional |
| | **Driver replaceability** | Replaceable by a professional |
| | **Accessibility of electronic components** | Tool-less |


| | | |
|---|---|---|
| Controls | **Dimming** | No dimming |

| | | |
|---|---|---|
| Approvals | **CE** | Yes |
| | **RoHS** | Yes |
| | **Ball-proof** | Yes |

Light distribution



Dimensions



Product images



