OWL Eco
OWE 300 740 L35 AB160 CJF NG2



Artikelnummer: 7760747
Vizulo artikelnr: 47103000

CE RoHS

Color RAL 7035

Electrical	**Input power**	300 W
	Input voltage	220 - 240 V
	Frequency	50 - 60 Hz
	Power factor	0.98
	Inrush current	160 A / 225 µs
	Stand-by power	0.32 W
Optical	**Optic name**	L35
	Distribution type	TYPE-IV
	Longitudinal classification	M
	Luminous flux	44716 lm ±7%
	Luminous efficacy	149 lm/W
	Performance temperature Tq	+25 °C
	Constant light output	No
	Color rendering index	>70
	Color temperature	4000 K
	Color tolerance	5 SDCM
	ULOR	0
	LED quantity	160
Lifetime	**Lumen depreciation**	L90 after 100 000 h
	Driver failure rate	<10% in 100 000 h
	Warranty	10 years
	Ambient temperature range	-40 ... +50 °C
Protection	**Protection class**	Class II


	Surge protection L-N	6 kV
	Surge protection L/N-PE	10 kV
	LED module thermal protection w/ NTC	No
	Max products per MCB B16	4
	Max products per MCB C16	6
	Ingress protection	IP66
	Impact resistance	IK08

Housing	**Body material**	Die-cast aluminium
	Cover material	Flat tempered glass
	Optic material	PMMA
	Color	RAL 7035 (light grey)
	Dimensions	533 x 655 x 85 mm
	Mounting	Standard
	LED module replaceability	Replaceable by a professional
	Driver replaceability	Replaceable by a professional
	Accessibility of electronic components	Tool-less


Controls	**Dimming**	No dimming

Approvals	**CE**	Yes
	RoHS	Yes
	Ball-proof	Yes

Light distribution



Dimensions



Product images





