

Martin family



RAL7035 RAL9006 DB703 RAL9005

Other colors on request

Body:	Die-cast aluminium	Installation:	Tool-less / Pre-wired cable 30 cm
Dimming:	DALI / 1-10 V / Midnight dimming / Step dimming / Mains dimming	Spigot:	Ø 40 - 60 / 60 - 76 mm
Voltage:	198 - 264 / 110 - 277 V, 50 - 60 Hz	Socket:	NEMA Top / Zhaga Top and Bottom
CRI:	>70 / >80 / >90	Intelligent control:	Stand-alone / Group / CMS
CCT:	2700 / 3000 / 4000 K ¹⁾	Sensor:	Motion / Motion + Daylight / Daylight
Temperature:	-40 up to +50 °C	Surge protection:	4 / 6 / 10 kV
Lifetime:	Up to 100 000 h (L98B10) at Ta = 25 °C	Nature friendly:	PC Amber / Red / 1800 K
Warranty:	5 years	Corrosion protection:	Up to C5
		Neto weight:	Up to 6.5 kg


¹⁾ Depending on the configuration. Please contact VIZULO export representatives for additional information
²⁾ Coming soon
³⁾ 1800 / 2200 / 3500 / 5000 / 5700 / 6500 K available on request along with other not listed CRI and CCT

MINI MARTIN RANGE




MINI MARTIN TOOL-LESS

Power: 5 - 145 W
Lumen output: Up to 19 755 lm



MINI MARTIN TOOL-LESS SMOOTH

Power: 5 - 130 W
Lumen output: Up to 18 260 lm




MICRO MARTIN RANGE




MICRO MARTIN (SCREW / TOOL-LESS VERSION)

Power: 5 - 115 W
Lumen output: Up to 15 030 lm



MICRO MARTIN SMOOTH (SCREW / TOOL-LESS VERSION)

Power: 5 - 95 W
Lumen output: Up to 13 070 lm



Mini Martin,
Watkins St, Merewether,
Australia