



Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).

Positioning Devices

COMPANY
PANDUIT CORP
16530 W 163RD ST
LOCKPORT, IL 60441-7606 United States

E56854

Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type	Bundle Dia.		Loop Tensile Str. N	Operating Temp. °C		Min. Install. Temp. °C	Resistant to UV Light	Air Handling Spaces	IEC 62275 Type
		mm			Min	Max				
		Min	Max							
Cable Tie (Composite)										
BT1.5M (f)(g)	2,21	1.6	38	80	-60	85	-20	-	AH-2	Type 2 Only
BT1.5M-0 (g)	2,21	1.6	38	80	-60	85	-20	Y	AH-2	Type 2 Only
BT1.5M-30 thru 39 (g)	2,21	1.6	38	80	-60	115	-20	-	-	Type 2 Only
BT1.5M-300 (g)	2	1.6	38	80	-60	115	-20	Y	AH-2	Type 2 Only
BT1.5M-XMR (f)(g)	2,21	1.6	33	133	-60	85	-20	-	AH-2	Type 2 Only
BT1.5M-XMR0 (g)	2,21	1.6	33	133	-60	85	-20	Y	AH-2	Type 2 Only
BT1.5M-XMR30 thru 39 (g)	2,21	1.6	33	133	-60	115	-20	-	-	Type 2 Only
BT1.5MG (f)(g)	2,21	1.6	38	80	-60	85	-20	-	AH-2	Type 2 Only

BT1.5MG-0 (g)	2,21	1.6	38	80	-60	85	-20	Y	AH-2	Type 2 Only
BT100 (f)(g)	2,21	1.6	23	80	-60	85	-20	-	AH-2	Type 2 Only
BT100B (g)	2,21	1.6	23	80	-60	85	-20	Y	AH-2	Type 2 Only
BT1M (f)(g)	2,21	1.6	23	80	-60	85	-20	-	AH-2	Type 2 Only
BT1M-0 (g)	2,21	1.6	23	80	-60	85	-20	Y	AH-2	Type 2 Only
BT1M-30 thru 39 (g)	2,21	1.6	23	80	-60	115	-20	-	-	Type 2 Only
BT1M-300 (g)	2	1.6	23	80	-60	115	-20	Y	AH-2	Type 2 Only
BT1M-XMR (f)(g)	2,21	1.6	21	133	-60	85	-20	-	AH-2	Type 2 Only
BT1M-XMR0 (g)	2,21	1.6	21	133	-60	85	-20	Y	AH-2	Type 2 Only
BT1M-XMR30 thru 39 (g)	2,21	1.6	21	133	-60	115	-20	-	-	Type 2 Only
BT1MG (f)(g)	2,21	1.6	23	80	-60	85	-20	-	AH-2	Type 2 Only
BT1MG-0 (g)	2,21	1.6	23	80	-60	85	-20	Y	AH-2	Type 2 Only
BT2M (f)(g)	2,21	1.6	51	80	-60	85	-20	-	AH-2	Type 2 Only
BT2M-0 (g)	2,21	1.6	51	80	-60	85	-20	Y	AH-2	Type 2 Only
BT2M-30 thru 39 (g)	2,21	1.6	51	80	-60	115	-20	-	-	Type 2 Only
BT2M-300 (g)	2	1.6	51	80	-60	115	-20	Y	AH-2	Type 2 Only
BT2MG (f)(g)	2,21	1.6	51	80	-60	85	-20	-	AH-2	Type 2 Only
BT2MG-0 (g)	2,21	1.6	51	80	-60	85	-20	Y	AH-2	Type 2 Only
BT4IG (f)(g)	2,21	0.8	102	178	-60	85	-20	-	AH-2	Type 2 Only
BT4IG-0 (g)	2,21	0.8	102	178	-60	85	-20	Y	AH-2	Type 2 Only

BT4M (f)(g)	2,21	1.6	102	80	-60	85	-20	-	AH-2	Type 2 Only
BT4M-0 (g)	2,21	1.6	102	80	-60	85	-20	Y	AH-2	Type 2 Only
BT4M-30 thru 39 (g)	2,21	1.6	102	80	-60	115	-20	-	-	Type 2 Only
BT4M-300 (g)	2	1.6	102	80	-60	115	-20	Y	AH-2	Type 2 Only
BT4MG (f)(g)	2,21	1.6	102	80	-60	85	-20	-	AH-2	Type 2 Only
BT4MG-0 (g)	2,21	1.6	102	80	-60	85	-20	Y	AH-2	Type 2 Only
Cable Tie (Nonmetallic)										
CBR1.5I (f)(g)	2,21	1.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
CBR1.5I-0 (g)	2,21	1.8	38	178	-60	85	-20	Y	-	Type 2 Only
CBR1.5I-30 thru 39 (g)	2,21	1.8	38	178	-60	115	-20	-	-	Type 2 Only
CBR1.5M (f)(g)	2,21	1.8	38	80	-60	85	-20	-	AH-2	Type 2 Only
CBR1.5M-0 (g)	2,21	1.8	38	80	-60	85	-20	Y	-	Type 2 Only
CBR1.5M-30 thru 39 (g)	2,21	1.8	38	80	-60	115	-20	-	-	Type 2 Only
CBR1M (f)(g)	2,21	1.8	25	80	-60	85	-20	-	AH-2	Type 2 Only
CBR1M-0 (g)	2,21	1.8	25	80	-60	85	-20	Y	-	Type 2 Only
CBR1M-30 thru 39 (g)	2,21	1.8	25	80	-60	115	-20	-	-	Type 2 Only
CBR2HS (f)(g)	2,21	4.1	51	378	-60	85	-20	-	AH-2	Type 2 Only
CBR2HS-0 (g)	2,21	4.1	51	378	-60	85	-20	Y	-	Type 2 Only
CBR2HS-30 thru 39 (g)	2,21	4.1	51	378	-60	115	-20	-	-	Type 2 Only
CBR2M (f)(g)	2,21	1.8	51	80	-60	85	-20	-	AH-2	Type 2 Only

CBR2M-0 (g)	2,21	1.8	51	80	-60	85	-20	Y	-	Type 2 Only
CBR2M-30 thru 39 (g)	2,21	1.8	51	80	-60	115	-20	-	-	Type 2 Only
CBR2S (f)(g)	2,21	4.1	51	222	-60	85	-20	-	AH-2	Type 2 Only
CBR2S-0 (g)	2,21	4.1	51	222	-60	85	-20	Y	-	Type 2 Only
CBR2S-30 thru 39 (g)	2,21	4.1	51	222	-60	115	-20	-	-	Type 2 Only
CBR3I (f)(g)	2,21	1.8	76	178	-60	85	-20	-	AH-2	Type 2 Only
CBR3I-0 (g)	2,21	1.8	76	178	-60	85	-20	Y	-	Type 2 Only
CBR3I-30 thru 39 (g)	2,21	1.8	76	178	-60	115	-20	-	-	Type 2 Only
CBR3S (f)(g)	2,21	7.1	76	222	-60	85	-20	-	AH-2	Type 2 Only
CBR3S-0 (g)	2,21	7.1	76	222	-60	85	-20	Y	-	Type 2 Only
CBR3S-30 thru 39 (g)	2,21	7.1	76	222	-60	115	-20	-	-	Type 2 Only
CBR4I (f)(g)	2,21	1.8	102	178	-60	85	-20	-	AH-2	Type 2 Only
CBR4I-0 (g)	2,21	1.8	102	178	-60	85	-20	Y	-	Type 2 Only
CBR4I-30 thru 39 (g)	2,21	1.8	102	178	-60	115	-20	-	-	Type 2 Only
CBR4LH (f)(g)	2,21	8.0	102	534	-60	85	-20	-	AH-2	Type 2 Only
CBR4LH-0 (g)	2,21	8.0	102	534	-60	85	-20	Y	-	Type 2 Only
CBR4LH-30 thru 39 (g)	2,21	8.0	102	534	-60	115	-20	-	-	Type 2 Only
CBR4S (f)(g)	2,21	7.1	102	222	-60	85	-20	-	AH-2	Type 2 Only
CBR4S-0 (g)	2,21	7.1	102	222	-60	85	-20	Y	-	Type 2 Only
CBR4S-30 thru 39 (g)	2,21	7.1	102	222	-60	115	-20	-	-	Type 2 Only

CBR6LH (f)(g)	2,21	8.0	152	534	-60	85	-20	-	AH-2	Type 2 Only
CBR6LH-0 (g)	2,21	8.0	152	534	-60	85	-20	Y	-	Type 2 Only
CBR6LH-30 thru 39 (g)	2,21	8.0	152	534	-60	115	-20	-	-	Type 2 Only
ILT200 (f)(g)	2,21	4.8	48	222	-60	85	-20	-	AH-2	Type 2 Only
ILT2S (f)(g)	2,21	4.8	48	222	-60	85	-20	-	AH-2	Type 2 Only
ILT2S-0 (g)	2,21	4.8	48	222	-60	85	-20	Y	-	Type 2 Only
ILT300 (f)(g)	2,21	4.8	76	222	-60	85	-20	-	AH-2	Type 2 Only
ILT350 (f)(g)	2,21	5.1	102	534	-60	85	-20	-	AH-2	Type 2 Only
ILT370S (f)(g)	2,21	4.8	102	222	-60	85	-20	-	AH-2	Type 2 Only
ILT3S (f)(g)	2,21	4.8	76	222	-60	85	-20	-	AH-2	Type 2 Only
ILT3S-0 (g)	2,21	4.8	76	222	-60	85	-20	Y	-	Type 2 Only
ILT4LH (f)(g)	2,21	5.1	102	534	-60	85	-20	-	AH-2	Type 2 Only
ILT4S (f)(g)	2,21	4.8	102	222	-60	85	-20	-	AH-2	Type 2 Only
ILT4S-0 (g)	2,21	4.8	102	222	-60	85	-20	Y	-	Type 2 Only
ILT6LH (f)(g)	2,21	5.1	152	534	-60	85	-20	-	AH-2	Type 2 Only
PLT.7M (f)(g)	2,21	1.6	17	80	-60	85	0	-	AH-2	Type 2 Only
PLT.7M (f)(g)	2,21	3.2	17	80	-60	85	-20	-	AH-2	Type 2 Only
PLT.7M-0 (g)	2,21	3.2	17	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT.7M-00 (g)	2,21	3.2	17	80	-60	85	-20	Y	-	Type 2 Only
PLT.7M-30 thru 39 (g)	2,21	3.2	17	80	-60	115	-20	-	-	Type 2 Only

PLT1.5I (f)(g)	2,21	1.6	35	178	-60	85	-20	-	AH-2	Type 2 Only
PLT1.5I-0 (g)	2,21	1.6	35	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT1.5I-00 (g)	2,21	1.6	35	178	-60	85	-20	Y	-	Type 2 Only
PLT1.5I-30 thru 39 (g)	2,21	1.6	35	178	-60	115	-20	-	-	Type 2 Only
PLT1.5I-300 (g)	2	1.6	35	178	-60	115	-20	Y	AH-2	Type 2 Only
PLT1.5M (f)(g)	2,21	1.6	32	80	-60	85	-20	-	AH-2	Type 2 Only
PLT1.5M-0 (g)	2,21	1.6	32	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT1.5M-00 (g)	2,21	1.6	32	80	-60	85	-20	Y	-	Type 2 Only
PLT1.5M-30 thru 39 (g)	2,21	1.6	32	80	-60	115	-20	-	-	Type 2 Only
PLT1.5S (f)(g)	2,21,2S,21S	1.6	38	222	-60	85	-20	-	AH-2	Type 2 Only
PLT1.5S-0 (g)	2,21,2S,21S	1.6	38	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT1.5S-00 (g)	2,21	1.6	38	222	-60	85	-20	Y	-	Type 2 Only
PLT1.5S-30 thru 39 (g)	2,21	1.6	38	222	-60	115	-20	-	-	Type 2 Only
PLT100 (f)(g)	2,21	0.8	23	80	-60	85	-20	-	AH-2	Type 2 Only
PLT100B (g)	2,21	0.8	23	80	-60	85	-20	Y	-	Type 2 Only
PLT10EH (f)(g)	2,21	63.5	254	1112	-60	85	0	-	AH-2	Type 2 Only
PLT10LH (f)(g)	2,21	4.8	262	534	-60	85	-20	-	AH-2	Type 2 Only
PLT10LH-0 (g)	2,21	4.8	262	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT10LH-00 (g)	2,21	4.8	262	534	-60	85	-20	Y	-	Type 2 Only
PLT10LH-30 thru 39 (g)	2,21	4.8	262	534	-60	115	-20	-	-	Type 2 Only

PLT10LHG (f)(g)	2,21	4.8	262	534	-60	85	-20	-	AH-2	Type 2 Only
PLT10LHG-0 (g)	2,21	4.8	262	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT12EH (f)(g)	2,21	63.5	305	1112	-60	85	0	-	AH-2	Type 2 Only
PLT150 (f)(g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
PLT150B (g)	2,21	0.8	38	178	-60	85	-20	Y	-	Type 2 Only
PLT1M (f)(g) (striped)	2,21	0.5	21	80	-60	85	-20	-	AH-2	Type 2 Only
PLT1M-0 (g)	2,21	1.6	22	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT1M-00 (g)	2,21	1.6	22	80	-60	85	-20	Y	-	Type 2 Only
PLT1M-30 thru 39 (g)	2,21	1.6	22	80	-60	115	-20	-	-	Type 2 Only
PLT1M-300 (g)	2	1.6	22	80	-60	115	-20	Y	AH-2	Type 2 Only
PLT1M-6120 (g)	2,21	1.5	22	89	-60	65	-20	Y	AH-2	Type 2 Only
PLT1M-702Y (g)	2,21	6.1	22	80	-60	125	-20	-	AH-2	Type 2 Only
PLT1S (f)(g)	2,21,2S,21S	3.18	25	222	-60	85	-20	-	AH-2	Type 2 Only
PLT1S-0 (g)	2,21,2S,21S	3.18	25	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT1S-00 (g)	2,21	3.18	25	222	-60	85	-20	Y	-	Type 2 Only
PLT1S-30 thru 39 (g)	2,21	3.18	25	222	-60	115	-20	-	-	Type 2 Only
PLT1S-300 (g)	2	3.18	25	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT2.5H (f)(g)	2,21	4.8	64	534	-60	85	-20	-	AH-2	Type 2 Only
PLT2.5H-0 (g)	2,21	4.8	64	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT2.5H-00 (g)	2,21	4.8	64	534	-60	85	-20	Y	-	Type 2 Only

PLT2.5H-30 thru 39 (g)	2,21	4.8	64	534	-60	115	-20	-	-	Type 2 Only
PLT2.5I (f)(g)	2,21	1.6	64	178	-60	85	-20	-	AH-2	Type 2 Only
PLT2.5I-0 (g)	2,21	1.6	64	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT2.5I-00 (g)	2,21	1.6	64	178	-60	85	-20	Y	-	Type 2 Only
PLT2.5I-30 thru 39 (g)	2,21	1.6	64	178	-60	115	-20	-	-	Type 2 Only
PLT2.5S (f)(g)	2,21,2S,21S	1.6	64	222	-60	85	-20	-	AH-2	Type 2 Only
PLT2.5S-0 (g)	2,21,2S,21S	1.6	64	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT2.5S-00 (g)	2,21	1.6	64	222	-60	85	-20	Y	-	Type 2 Only
PLT2.5S-300 (g)	2	1.6	64	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT200 (f)(g)	2,21	1.6	51	222	-60	85	-20	-	AH-2	Type 2 Only
PLT200B (g)	2,21	1.6	51	222	-60	85	-20	Y	-	Type 2 Only
PLT250 (f)(g)	2,21	4.1	66	334	-60	85	-20	-	AH-2	Type 2 Only
PLT250B (g)	2,21	4.1	66	334	-60	85	-20	Y	-	Type 2 Only
PLT2EH (f)(g)	2,21	12.7	51	1112	-60	85	0	-	AH-2	Type 2 Only
PLT2H (f)(g)	2,21	4.8	51	534	-60	85	-20	-	AH-2	Type 2 Only
PLT2H-0 (g)	2,21	4.8	51	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT2H-00 (g)	2,21	4.8	51	534	-60	85	-20	Y	-	Type 2 Only
PLT2H-30 thru 39 (g)	2,21	4.8	51	534	-60	115	-20	-	-	Type 2 Only
PLT2H-300 (g)	2	4.8	51	534	-60	115	-20	Y	AH-2	Type 2 Only
PLT2I (f)(g)	2,21	1.6	51	178	-60	85	-20	-	AH-2	Type 2 Only

PLT2I-0 (g)	2,21	1.6	51	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT2I-00 (g)	2,21	1.6	51	178	-60	85	-20	Y	-	Type 2 Only
PLT2I-30 thru 39 (g)	2,21	1.6	51	178	-60	115	-20	-	-	Type 2 Only
PLT2I-300 (g)	2	1.6	51	178	-60	115	-20	Y	AH-2	Type 2 Only
PLT2M (f)(g)	2,21	1.6	51	80	-60	85	-20	-	AH-2	Type 2 Only
PLT2M-0 (g)	2,21	1.6	51	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT2M-00 (g)	2,21	1.6	51	80	-60	85	-20	Y	-	Type 2 Only
PLT2M-30 thru 39 (g)	2,21	1.6	51	80	-60	115	-20	-	-	Type 2 Only
PLT2M-300 (g)	2	1.6	51	80	-60	115	-20	Y	AH-2	Type 2 Only
PLT2S (f)(g)	2,21,2S,21S	1.6	48	222	-60	85	-20	-	AH-2	Type 2 Only
PLT2S-0 (g)	2,21,2S,21S	1.6	48	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT2S-00 (g)	2,21	1.6	48	222	-60	85	-20	Y	-	Type 2 Only
PLT2S-30 thru 39 (g)	2,21	1.6	48	222	-60	115	-20	-	-	Type 2 Only
PLT2S-300 (g)	2	3.18	48	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT2S-702Y (g)	2,21,2S,21S	1.6	48	222	-60	125	-20	-	AH-2	Type 2 Only
PLT300 (f)(g)	2,21	4.1	81	334	-60	85	-20	-	AH-2	Type 2 Only
PLT300B (g)	2,21	4.1	81	334	-60	85	-20	Y	-	Type 2 Only
PLT350 (f)(g)	2,21	4.8	105	534	-60	85	-20	-	AH-2	Type 2 Only
PLT350B (g)	2,21	4.8	105	534	-60	85	-20	Y	-	Type 2 Only
PLT370S (f)(g)	2,21	4.1	107	334	-60	85	-20	-	AH-2	Type 2 Only

PLT370SB (g)	2,21	4.1	107	334	-60	85	-20	Y	-	Type 2 Only
PLT3H (f)(g)	2,21	4.8	76	534	-60	85	-20	-	AH-2	Type 2 Only
PLT3H-0 (g)	2,21	4.8	76	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT3H-00 (g)	2,21	4.8	76	534	-60	85	-20	Y	-	Type 2 Only
PLT3H-30 thru 39 (g)	2,21	4.8	76	534	-60	115	-20	-	-	Type 2 Only
PLT3I (f)(g)	2,21	1.6	76	178	-60	85	-20	-	AH-2	Type 2 Only
PLT3I-0 (g)	2,21	1.6	76	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT3I-00 (g)	2,21	1.6	76	178	-60	85	-20	Y	-	Type 2 Only
PLT3I-30 thru 39 (g)	2,21	1.6	76	178	-60	115	-20	-	-	Type 2 Only
PLT3S (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	-20	-	AH-2	Type 2 Only
PLT3S-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT3S-00 (g)	2,21	1.6	76	222	-60	85	-20	Y	-	Type 2 Only
PLT3S-30 thru 39 (g)	2,21	1.6	76	222	-60	115	-20	-	-	Type 2 Only
PLT3S-300 (g)	2	1.6	76	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT3S-702Y (g)	2,21,2S,21S	1.6	76	222	-60	125	-20	-	AH-2	Type 2 Only
PLT4.5S (f)(g)	2,21,2S,21S	1.6	114	222	-60	85	-20	-	AH-2	Type 2 Only
PLT4.5S-0 (g)	2,21,2S,21S	1.6	114	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT4.5S-00 (g)	2,21	1.6	114	222	-60	85	-20	Y	-	Type 2 Only
PLT4.5S-30 thru 39 (g)	2,21	1.6	114	222	-60	115	-20	-	-	Type 2 Only
PLT4.5S-300 (g)	2	1.6	114	222	-60	115	-20	Y	AH-2	Type 2 Only

PLT450 (f)(g)	2,21	4.8	132	778	-60	85	-20	-	AH-2	Type 2 Only
PLT4H (f)(g)	2,21	4.8	102	534	-60	85	-20	-	AH-2	Type 2 Only
PLT4H-0 (g)	2,21	4.8	102	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT4H-00 (g)	2,21	4.8	102	534	-60	85	-20	Y	-	Type 2 Only
PLT4H-30 thru 39 (g)	2,21	4.8	102	534	-60	115	-20	-	-	Type 2 Only
PLT4H-300 (g)	2	4.8	102	534	-60	115	-20	Y	AH-2	Type 2 Only
PLT4I (f)(g)	2,21	1.6	102	178	-60	85	-20	-	AH-2	Type 2 Only
PLT4I-0 (g)	2,21	1.6	102	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT4I-00 (g)	2,21	1.6	102	178	-60	85	-20	Y	-	Type 2 Only
PLT4I-30 thru 39 (g)	2,21	1.6	102	178	-60	115	-20	-	-	Type 2 Only
PLT4S (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	-20	-	AH-2	Type 2 Only
PLT4S-0 (g)	2,21,2S,21S	1.6	102	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT4S-00 (g)	2,21	1.6	102	222	-60	85	-20	Y	-	Type 2 Only
PLT4S-30 thru 39 (g)	2,21	1.6	102	222	-60	115	-20	-	-	Type 2 Only
PLT4S-300 (g)	2	1.6	102	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT510 (f)(g)	2,21	12.7	127	1112	-60	85	0	-	AH-2	Type 2 Only
PLT550 (f)(g)	2,21	12.7	152	1112	-60	85	0	-	AH-2	Type 2 Only
PLT5EH (f)(g)	2,21	12.7	127	1112	-60	85	0	-	AH-2	Type 2 Only
PLT5S (f)(g)	2,21,2S,21S	1.6	127	222	-60	85	-20	-	AH-2	Type 2 Only
PLT5S-0 (g)	2,21,2S,21S	1.6	127	222	-60	85	-20	Y	AH-2	Type 2 Only

PLT5S-00 (g)	2,21	1.6	127	222	-60	85	-20	Y	-	Type 2 Only
PLT5S-30 thru 39 (g)	2,21	1.6	127	222	-60	115	-20	-	-	Type 2 Only
PLT5S-300 (g)	2	1.6	127	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT6EH (f)(g)	2,21	12.7	152	1112	-60	85	0	-	AH-2	Type 2 Only
PLT6LH (f)(g)	2,21	4.8	152	534	-60	85	-20	-	AH-2	Type 2 Only
PLT6LH-0 (g)	2,21	4.8	152	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT6LH-00 (g)	2,21	4.8	152	534	-60	85	-20	Y	-	Type 2 Only
PLT6LH-30 thru 39 (g)	2,21	4.8	152	534	-60	115	-20	-	-	Type 2 Only
PLT6LHG (f)(g)	2,21	4.8	152	534	-60	85	-20	-	AH-2	Type 2 Only
PLT6LHG-0 (g)	2,21	4.8	152	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT7LH (f)(g)	2,21	4.8	178	534	-60	85	-20	-	AH-2	Type 2 Only
PLT7LH-0 (g)	2,21	4.8	178	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT7LH-00 (g)	2,21	4.8	178	534	-60	85	-20	Y	-	Type 2 Only
PLT7LH-30 thru 39 (g)	2,21	4.8	178	534	-60	115	-20	-	-	Type 2 Only
PLT7LHG (f)(g)	2,21	4.8	178	534	-60	85	-20	-	AH-2	Type 2 Only
PLT7LHG-0 (g)	2,21	4.8	178	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT80 (f)(g)	2,21	3.2	17	80	-60	85	-20	-	AH-2	Type 2 Only
PLT80B (g)	2,21	3.2	17	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT8EH (f)(g)	2,21	63.5	203	1112	-60	85	0	-	AH-2	Type 2 Only
PLT8LH (f)(g)	2,21	4.8	203	534	-60	85	-20	-	AH-2	Type 2 Only

PLT8LH-0 (g)	2,21	4.8	203	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT8LH-00 (g)	2,21	4.8	203	534	-60	85	-20	Y	-	Type 2 Only
PLT8LH-30 thru 39 (g)	2,21	4.8	203	534	-60	115	-20	-	-	Type 2 Only
PLT8LHG (f)(g)	2,21	4.8	203	534	-60	85	-20	-	AH-2	Type 2 Only
PLT8LHG-0 (g)	2,21	4.8	203	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT9LH (f)(g)	2,21	4.8	229	534	-60	85	-20	-	AH-2	Type 2 Only
PLT9LH-0 (g)	2,21	4.8	229	534	-60	85	-20	Y	AH-2	Type 2 Only
PLT9LH-00 (g)	2,21	4.8	229	534	-60	85	-20	Y	-	Type 2 Only
PLT9LH-30 thru 39 (g)	2,21	4.8	229	534	-60	115	-20	-	-	Type 2 Only
PLT9LH-300 (g)	2	4.8	229	534	-60	115	-20	Y	AH-2	Type 2 Only
PLT9LHG (f)(g)	2,21	4.8	229	534	-60	85	-20	-	AH-2	Type 2 Only
PLT9LHG-0 (g)	2,21	4.8	229	534	-60	85	-20	Y	AH-2	Type 2 Only
PRT1.5S (f)(g)	2,21,2S,21S	1.6	38	222	-60	85	-20	-	AH-2	Type 2 Only
PRT1.5S-0 (g)	2,21,2S,21S	1.6	38	222	-60	85	-20	Y	AH-2	Type 2 Only
PRT1.5S-00 (g)	2,21	1.6	38	222	-60	85	-20	Y	-	Type 2 Only
PRT1.5S-30 thru 39 (g)	2,21	1.6	38	222	-60	115	-20	-	-	Type 2 Only
PRT1.5S-300 (g)	2	1.6	38	222	-60	115	-20	Y	AH-2	Type 2 Only
PRT10EH (f)(g)	2,21	63.5	254	1112	-60	85	0	-	AH-2	Type 2 Only
PRT12EH (f)(g)	2,21	63.5	305	1112	-60	85	0	-	AH-2	Type 2 Only
PRT1S (f)(g)	2,21,2S,21S	1.6	25	222	-60	85	-20	-	AH-2	Type 2 Only

PRT1S-0 (g)	2,21,2S,21S	1.6	25	222	-60	85	-20	Y	AH-2	Type 2 Only
PRT1S-00 (g)	2,21	1.6	25	222	-60	85	-20	Y	-	Type 2 Only
PRT1S-30 thru 39 (g)	2,21	1.6	25	222	-60	115	-20	-	-	Type 2 Only
PRT1S-300 (g)	2	1.6	25	222	-60	115	-20	Y	AH-2	Type 2 Only
PRT2EH (f)(g)	2,21	12.7	51	1112	-60	85	0	-	AH-2	Type 2 Only
PRT2S (f)(g)	2,21,2S,21S	1.6	48	222	-60	85	-20	-	AH-2	Type 2 Only
PRT2S-0 (g)	2,21,2S,21S	3.18	48	222	-60	85	-20	Y	AH-2	Type 2 Only
PRT2S-00 (g)	2,21	1.6	48	222	-60	85	-20	Y	-	Type 2 Only
PRT2S-30 thru 39 (g)	2,21	1.6	48	222	-60	115	-20	-	-	Type 2 Only
PRT2S-300 (g)	2	1.6	48	222	-60	115	-20	Y	AH-2	Type 2 Only
PRT3S (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	-20	-	AH-2	Type 2 Only
PRT3S-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	-20	Y	AH-2	Type 2 Only
PRT3S-00 (g)	2,21	1.6	76	222	-60	85	-20	Y	-	Type 2 Only
PRT3S-30 thru 39 (g)	2,21	1.6	76	222	-60	115	-20	-	-	Type 2 Only
PRT3S-300 (g)	2	1.6	76	222	-60	115	-20	Y	AH-2	Type 2 Only
PRT4S (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	-20	-	AH-2	Type 2 Only
PRT4S-0 (g)	2,21,2S,21S	1.6	102	222	-60	85	-20	Y	AH-2	Type 2 Only
PRT4S-00 (g)	2,21	1.6	102	222	-60	85	-20	Y	-	Type 2 Only
PRT4S-30 thru 39 (g)	2,21	1.6	102	222	-60	115	-20	-	-	Type 2 Only
PRT4S-300 (g)	2	1.6	102	222	-60	115	-20	Y	AH-2	Type 2 Only

PRT5EH (f)(g)	2,21	12.7	127	1112	-60	85	0	-	AH-2	Type 2 Only
PRT6EH (f)(g)	2,21	12.7	152	1112	-60	85	0	-	AH-2	Type 2 Only
PRT8EH (f)(g)	2,21	63.5	203	1112	-60	85	0	-	AH-2	Type 2 Only
SG100M (f)(g)	2,21	0.8	23	80	-60	85	-20	-	AH-2	Type 2 Only
SG100M-0 (g)	2,21	0.8	23	80	-60	85	-20	Y	-	Type 2 Only
SG100MG (f)(g)	2,21	0.8	23	80	-60	85	-20	-	AH-2	Type 2 Only
SG100MG-0 (g)	2,21	0.8	23	80	-60	85	-20	Y	-	Type 2 Only
SG150I (f)(g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
SG150I-0 (g)	2,21	0.8	38	178	-60	85	-20	Y	-	Type 2 Only
SG150IG (f)(g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
SG150IG-0 (g)	2,21	0.8	38	178	-60	85	-20	Y	-	Type 2 Only
SG200S (f)(g)	2,21	1.6	51	222	-60	85	-20	-	AH-2	Type 2 Only
SG200S-0 (g)	2,21	1.6	51	222	-60	85	-20	Y	-	Type 2 Only
SG200SG (f)(g)	2,21	1.6	51	222	-60	85	-20	-	AH-2	Type 2 Only
SG200SG-0 (g)	2,21	1.6	51	222	-60	85	-20	Y	-	Type 2 Only
SG250S (f)(g)	2,21	4.1	66	334	-60	85	-20	-	AH-2	Type 2 Only
SG250S-0 (g)	2,21	4.1	66	334	-60	85	-20	Y	-	Type 2 Only
SG300S (f)(g)	2,21	4.1	81	334	-60	85	-20	-	AH-2	Type 2 Only
SG300S-0 (g)	2,21	4.1	81	334	-60	85	-20	Y	-	Type 2 Only
SG300SG (f)(g)	2,21	4.1	81	334	-60	85	-20	-	AH-2	Type 2 Only

SG300SG-0 (g)	2,21	4.1	81	334	-60	85	-20	Y	-	Type 2 Only
SG350LH (f)(g)	2,21	4.8	105	534	-60	85	-20	-	AH-2	Type 2 Only
SG350LH-0 (g)	2,21	4.8	105	534	-60	85	-20	Y	-	Type 2 Only
SG350LHG (f)(g)	2,21	4.8	105	534	-60	85	-20	-	AH-2	Type 2 Only
SG350LHG-0 (g)	2,21	4.8	105	534	-60	85	-20	Y	-	Type 2 Only
SG370S (f)(g)	2,21	4.1	107	334	-60	85	-20	-	AH-2	Type 2 Only
SG370S-0 (g)	2,21	4.1	107	334	-60	85	-20	Y	-	Type 2 Only
SG370SG (f)(g)	2,21	4.1	107	334	-60	85	-20	-	AH-2	Type 2 Only
SG370SG-0 (g)	2,21	4.1	107	334	-60	85	-20	Y	-	Type 2 Only
SG450H (f)(g)	2,21	4.8	132	778	-60	85	-20	-	AH-2	Type 2 Only
SG450HG (f)(g)	2,21	4.8	132	778	-60	85	-20	-	AH-2	Type 2 Only
Composite Cable Ties										
BT1.5I (f)(g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
BT1.5I-0 (g)	2,21	0.8	38	178	-60	85	-20	Y	AH-2	Type 2 Only
BT1.5I-30 thru 39 (g)	2,21	0.8	38	178	-60	115	-20	-	-	Type 2 Only
BT1.5I-300 (g)	2	0.8	38	178	-60	115	-20	Y	AH-2	Type 2 Only
BT1.5IG (f)(g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
BT1.5IG-0 (g)	2,21	0.8	38	178	-60	85	-20	Y	AH-2	Type 2 Only
BT150 (f)(g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
BT150B (g)	2,21	0.8	38	178	-60	85	-20	Y	AH-2	Type 2 Only

BT200 (f)(g)	2,21,2S,21S	1.6	51	222	-60	85	-20	-	AH-2	Type 2 Only
BT200B (g)	2,21,2S,21S	1.6	51	222	-60	85	-20	Y	AH-2	Type 2 Only
BT21 (f)(g)	2,21	0.8	51	178	-60	85	-20	-	AH-2	Type 2 Only
BT21-0 (g)	2,21	0.8	51	178	-60	85	-20	Y	AH-2	Type 2 Only
BT21-30 thru 39 (g)	2,21	0.8	51	178	-60	115	-20	-	-	Type 2 Only
BT21-300 (g)	2	0.8	51	178	-60	115	-20	Y	AH-2	Type 2 Only
BT21G (f)(g)	2,21	0.8	51	178	-60	85	-20	-	AH-2	Type 2 Only
BT21G-0 (g)	2,21	0.8	51	178	-60	85	-20	Y	AH-2	Type 2 Only
BT21H (f)(g)	2,21,2S,21S	4.8	51	534	-60	85	-20	-	AH-2	Type 2 Only
BT21H-0 (g)	2,21,2S,21S	4.8	51	534	-60	85	-20	Y	AH-2	Type 2 Only
BT21H-30 thru 39 (g)	2,21	4.8	51	534	-60	115	-20	-	-	Type 2 Only
BT21H-300 (g)	2	4.8	51	534	-60	115	-20	Y	AH-2	Type 2 Only
BT21HG (f)(g)	2,21,2S,21S	4.8	51	534	-60	85	-20	-	AH-2	Type 2 Only
BT21HG-0 (g)	2,21,2S,21S	4.8	51	534	-60	85	-20	Y	AH-2	Type 2 Only
BT2S (f)(g)	2,21,2S,21S	1.6	51	222	-60	85	-20	-	AH-2	Type 2 Only
BT2S-0 (g)	2,21,2S,21S	1.6	51	222	-60	85	-20	Y	AH-2	Type 2 Only
BT2S-30 thru 39 (g)	2,21	1.6	51	222	-60	115	-20	-	-	Type 2 Only
BT2S-300 (g)	2	1.6	51	222	-60	115	-20	Y	AH-2	Type 2 Only
BT2SG (f)(g)	2,21,2S,21S	1.6	51	222	-60	85	-20	-	AH-2	Type 2 Only
BT2SG-0 (g)	2,21,2S,21S	1.6	51	222	-60	85	-20	Y	AH-2	Type 2 Only

BT300B (g)	2,21,2S,21S	1.6	76	222	-60	85	-20	Y	AH-2	Type 2 Only
BT300S (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	-20	-	AH-2	Type 2 Only
BT350 (f)(g)	2,21,2S,21S	4.8	102	534	-60	85	-20	-	AH-2	Type 2 Only
BT350B (g)	2,21,2S,21S	4.8	102	534	-60	85	-20	Y	AH-2	Type 2 Only
BT370S (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	-20	-	AH-2	Type 2 Only
BT370SB (g)	2,21,2S,21S	1.6	102	222	-60	85	-20	Y	AH-2	Type 2 Only
BT3I (f)(g)	2,21	0.8	76	178	-60	85	-20	-	AH-2	Type 2 Only
BT3I-0 (g)	2,21	0.8	76	178	-60	85	-20	Y	AH-2	Type 2 Only
BT3I-30 thru 39 (g)	2,21	0.8	76	178	-60	115	-20	-	-	Type 2 Only
BT3I-300 (g)	2	0.8	76	178	-60	115	-20	Y	AH-2	Type 2 Only
BT3IG (f)(g)	2,21	0.8	76	178	-60	85	-20	-	AH-2	Type 2 Only
BT3IG-0 (g)	2,21	0.8	76	178	-60	85	-20	Y	AH-2	Type 2 Only
BT3LH (f)(g)	2,21,2S,21S	4.8	76	534	-60	85	-20	-	AH-2	Type 2 Only
BT3LH-0 (g)	2,21,2S,21S	4.8	76	534	-60	85	-20	Y	AH-2	Type 2 Only
BT3LH-30 thru 39 (g)	2,21	4.8	76	534	-60	115	-20	-	-	Type 2 Only
BT3LH-300 (g)	2	4.8	76	534	-60	115	-20	Y	AH-2	Type 2 Only
BT3S (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	-20	-	AH-2	Type 2 Only
BT3S-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	-20	Y	AH-2	Type 2 Only
BT3S-30 thru 39 (g)	2,21	1.6	76	222	-60	115	-20	-	-	Type 2 Only
BT3S-300 (g)	2	1.6	76	222	-60	115	-20	Y	AH-2	Type 2 Only

BT3SG (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	-20	-	AH-2	Type 2 Only
BT3SG-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	-20	Y	AH-2	Type 2 Only
BT450 (f)(g)	2,21,2S,21S	4.8	127	534	-60	85	-20	-	AH-2	Type 2 Only
BT4I (f)(g)	2,21	0.8	102	178	-60	85	-20	-	AH-2	Type 2 Only
BT4I-0 (g)	2,21	0.8	102	178	-60	85	-20	Y	AH-2	Type 2 Only
BT4I-30 thru 39 (g)	2,21	0.8	102	178	-60	115	-20	-	-	Type 2 Only
BT4I-300 (g)	2	0.8	102	178	-60	115	-20	Y	AH-2	Type 2 Only
BT4LH (f)(g)	2,21,2S,21S	4.8	102	534	-60	85	-20	-	AH-2	Type 2 Only
BT4LH-0 (g)	2,21,2S,21S	4.8	102	534	-60	85	-20	Y	AH-2	Type 2 Only
BT4LH-30 thru 39 (g)	2,21	4.8	102	534	-60	115	-20	-	-	Type 2 Only
BT4LH-300 (g)	2	4.8	102	534	-60	115	-20	Y	AH-2	Type 2 Only
BT4LHG (f)(g)	2,21,2S,21S	4.8	102	534	-60	85	-20	-	AH-2	Type 2 Only
BT4LHG-0 (g)	2,21,2S,21S	4.8	102	534	-60	85	-20	Y	AH-2	Type 2 Only
BT4S (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	-20	-	AH-2	Type 2 Only
BT4S-0 (g)	2,21,2S,21S	1.6	102	222	-60	85	-20	Y	AH-2	Type 2 Only
BT4S-30 thru 39 (g)	2,21	1.6	102	222	-60	115	-20	-	-	Type 2 Only
BT4S-300 (g)	2	1.6	102	222	-60	115	-20	Y	AH-2	Type 2 Only
BT4SG (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	-20	-	AH-2	Type 2 Only
BT4SG-0 (g)	2,21,2S,21S	1.6	102	222	-60	85	-20	Y	AH-2	Type 2 Only
BT550 (f)(g)	2,21,2S,21S	4.8	152	534	-60	85	-20	-	AH-2	Type 2 Only

BT5LH (f)(g)	2,21,2S,21S	4.8	127	534	-60	85	-20	-	AH-2	Type 2 Only
BT5LH-0 (g)	2,21,2S,21S	4.8	127	534	-60	85	-20	Y	AH-2	Type 2 Only
BT5LH-30 thru 39 (g)	2,21	4.8	127	534	-60	115	-20	-	-	Type 2 Only
BT5LH-300 (g)	2	4.8	127	534	-60	115	-20	Y	AH-2	Type 2 Only
BT5LHG (f)(g)	2,21,2S,21S	4.8	127	534	-60	85	-20	-	AH-2	Type 2 Only
BT5LHG-0 (g)	2,21,2S,21S	4.8	127	534	-60	85	-20	Y	AH-2	Type 2 Only
BT600 (f)(g)	2,21,2S,21S	4.8	178	534	-60	85	-20	-	AH-2	Type 2 Only
BT6LH (f)(g)	2,21,2S,21S	4.8	152	534	-60	85	-20	-	AH-2	Type 2 Only
BT6LH-0 (g)	2,21,2S,21S	4.8	152	534	-60	85	-20	Y	AH-2	Type 2 Only
BT6LH-30 thru 39 (g)	2,21	4.8	152	534	-60	115	-20	-	-	Type 2 Only
BT6LH-300 (g)	2	4.8	152	534	-60	115	-20	Y	AH-2	Type 2 Only
BT6LHG (f)(g)	2,21,2S,21S	4.8	152	534	-60	85	-20	-	AH-2	Type 2 Only
BT6LHG-0 (g)	2,21,2S,21S	4.8	152	534	-60	85	-20	Y	AH-2	Type 2 Only
BT700 (f)(g)	2,21,2S,21S	4.8	203	534	-60	85	-20	-	AH-2	Type 2 Only
BT7LH (f)(g)	2,21,2S,21S	4.8	178	534	-60	85	-20	-	AH-2	Type 2 Only
BT7LH-0 (g)	2,21,2S,21S	4.8	178	534	-60	85	-20	Y	AH-2	Type 2 Only
BT7LH-30 thru 39 (g)	2,21	4.8	178	534	-60	115	-20	-	-	Type 2 Only
BT7LH-300 (g)	2	4.8	178	534	-60	115	-20	Y	AH-2	Type 2 Only
BT7LHG (f)(g)	2,21,2S,21S	4.8	178	534	-60	85	-20	-	AH-2	Type 2 Only
BT7LHG-0 (g)	2,21,2S,21S	4.8	178	534	-60	85	-20	Y	AH-2	Type 2 Only

BT800 (f)(g)	2,21,2S,21S	4.8	229	534	-60	85	-20	-	AH-2	Type 2 Only
BT8LH (f)(g)	2,21,2S,21S	4.8	203	534	-60	85	-20	-	AH-2	Type 2 Only
BT8LH-0 (g)	2,21,2S,21S	4.8	203	534	-60	85	-20	Y	AH-2	Type 2 Only
BT8LH-30 thru 39 (g)	2,21	4.8	203	534	-60	115	-20	-	-	Type 2 Only
BT8LH-300 (g)	2	4.8	203	534	-60	115	-20	Y	AH-2	Type 2 Only
BT8LHG (f)(g)	2,21,2S,21S	4.8	203	534	-60	85	-20	-	AH-2	Type 2 Only
BT8LHG-0 (g)	2,21,2S,21S	4.8	203	534	-60	85	-20	Y	AH-2	Type 2 Only
BT9LH (f)(g)	2,21,2S,21S	4.8	229	534	-60	85	-20	-	AH-2	Type 2 Only
BT9LH-0 (g)	2,21,2S,21S	4.8	229	534	-60	85	-20	Y	AH-2	Type 2 Only
BT9LH-30 thru 39 (g)	2,21	4.8	229	534	-60	115	-20	-	-	Type 2 Only
BT9LH-300 (g)	2	4.8	229	534	-60	115	-20	Y	AH-2	Type 2 Only
BT9LHG (f)(g)	2,21,2S,21S	4.8	229	534	-60	85	-20	-	AH-2	Type 2 Only
BT9LHG-0 (g)	2,21,2S,21S	4.8	229	534	-60	85	-20	Y	AH-2	Type 2 Only
Composite Cable Ties with Integral Screw Mount Fixing Device										
BC1.5I-S8 (f) (g)	2,21	0.8	38	178	-60	85	-20	-	AH-2	Type 2 Only
Metallic Cable Ties (coated stainless steel)										
IMLTFCxH (a)(d)	21,21S	25.4	1270	890	-	150	-	Y	AH-1	Type 2 Only
IMLTFCxS (a)(d)	21,21S	12.7	1270	445	-	150	-	Y	AH-1	Type 2 Only
IMSBL12 (a) + IMSP12T35 (b) (i)										
	21,21S	25.4	-	2445	-	150	-	Y	AH-1	Type 2 Only
IMSBL16 (a) + IMSP16T35 (b) (i)										

	21,21S	25.4	-	3115	-	150	-	Y	AH-1	Type 2 Only
IMSB L9.5 (a) + IMSP9.5T35 (b) (i)										
	21,21S	25.4	-	1780	-	150	-	Y	AH-1	Type 2 Only
MLTCxH (a)(c)	21,21S	12.7	1270	1112	-	140	-	Y	AH-1	Type 2 Only
MLTFCxEH (a)(c)	21,21S	25.4	1270	1335	-	150	-	Y	AH-1	Type 2 Only
MLTFCxH (a)(c)	21,21S	12.7	1270	1112	-	150	-	Y	AH-1	Type 2 Only
MLTFCxS (a)(c)	21,21S	12.7	1270	445	-	150	-	Y	AH-1	Type 2 Only
MLTFCxSH (a)(c)	21,21S	25.4	1270	2000	-	150	-	Y	AH-1	Type 2 Only
MSBW38 (a) + MSCNW38T15 (b) (i)										
	21,21S	25.4	-	2225	-	140	-	Y	AH-1	Type 2 Only
MSBW50 (a) + MSCNW50T15 (b) (i)										
	21,21S	25.4	-	3115	-	140	-	Y	AH-1	Type 2 Only
MSBW63 (a) + MSCNW63T15 (b) (i)										
	21,21S	25.4	-	3560	-	140	-	Y	AH-1	Type 2 Only
MSC10W38T15 (a)	21,21S	25.4	254	2225	-	140	-	Y	AH-1	Type 2 Only
MSC10W50T15 (a)	21,21S	25.4	254	3115	-	140	-	Y	AH-1	Type 2 Only
MSC10W63T15 (a)	21,21S	25.4	254	3560	-	140	-	Y	AH-1	Type 2 Only
MSC2W38T15 (a)	21,21S	25.4	50.8	2225	-	140	-	Y	AH-1	Type 2 Only
MSC4W38T15 (a)	21,21S	25.4	101.6	2225	-	140	-	Y	AH-1	Type 2 Only
MSC4W50T15 (a)	21,21S	25.4	101.6	3115	-	140	-	Y	AH-1	Type 2 Only
MSC4W63T15 (a)	21,21S	25.4	101.6	3560	-	140	-	Y	AH-1	Type 2 Only

MSC6W38T15 (a)	21,21S	25.4	152.4	2225	-	140	-	Y	AH-1	Type 2 Only
MSC6W50T15 (a)	21,21S	25.4	152.4	3115	-	140	-	Y	AH-1	Type 2 Only
MSC6W63T15 (a)	21,21S	25.4	152.4	3560	-	140	-	Y	AH-1	Type 2 Only
MSC8W38T15 (a)	21,21S	25.4	203.2	2225	-	140	-	Y	AH-1	Type 2 Only
MSC8W50T15 (a)	21,21S	25.4	203.2	3115	-	140	-	Y	AH-1	Type 2 Only
MSC8W63T15 (a)	21,21S	25.4	203.2	3560	-	140	-	Y	AH-1	Type 2 Only
Metallic Cable Ties (uncoated stainless steel)										
HTMLTxWEH (a)(c)	2,2S	50.8	1270	2670	-	300	-	Y	AH-1	Type 2 Only
IMBL12 (a) + IMS12T35 (b) (i)	2,2S	25.4	-	2445	-	300	-	Y	AH-1	Type 2 Only
IMLTxH (a)(d)	2,2S	12.7	1270	890	-	300	-	Y	AH-1	Type 2 Only
IMLTxS (a)(d)	2,2S	12.7	1270	556	-	300	-	Y	AH-1	Type 2 Only
IMSBE19 (a) + IMS19T75 (b) (i)	2,2S	25.4	-	4225	-	300	-	Y	AH-1	Type 2 Only
IMSBL16 (a) + IMS16T35 (b) (i)	2,2S	25.4	-	3110	-	300	-	Y	AH-1	Type 2 Only
IMSBL9.5 (a) + IMS9.5T35 (b) (i)										
	2,2S	25.4	-	1780	-	300	-	Y	AH-1	Type 2 Only
MLT10H (a)	2,2S	12.7	254	2000	-	300	-	Y	AH-1	Type 2 Only
MLT10LH (a)	2,2S	12.7	254	1112	-	300	-	Y	AH-1	Type 2 Only
MLT10S (a)	2,2S	12.7	254	890	-	300	-	Y	AH-1	Type 2 Only
MLT12H (a)	2,2S	12.7	304.8	2000	-	300	-	Y	AH-1	Type 2 Only
MLT12LH (a)	2,2S	12.7	304.8	1112	-	300	-	Y	AH-1	Type 2 Only
MLT12S (a)	2,2S	12.7	304.8	890	-	300	-	Y	AH-1	Type 2 Only

MLT14H (a)	2,2S	12.7	355.6	2000	-	300	-	Y	AH-1	Type 2 Only
MLT14LH (a)	2,2S	12.7	355.6	1112	-	300	-	Y	AH-1	Type 2 Only
MLT14S (a)	2,2S	12.7	355.6	-	-	300	-	Y	AH-1	Type 2 Only
MLT15S (a)	2,2S	12.7	381	890	-	300	-	Y	AH-1	Type 2 Only
MLT1S (a)	2,2S	12.7	25.4	890	-	300	-	Y	AH-1	Type 2 Only
MLT2.7H (a)	2,2S	12.7	68.6	2000	-	300	-	Y	AH-1	Type 2 Only
MLT2.7LH (a)	2,2S	12.7	68.6	1112	-	300	-	Y	AH-1	Type 2 Only
MLT2.7S (a)	2,2S	12.7	68.6	890	-	300	-	Y	AH-1	Type 2 Only
MLT2.7WH (a)	2,2S	50.8	68.6	2000	-	300	-	Y	AH-1	Type 2 Only
MLT2.7WLH (a)	2,2S	50.8	68.6	1112	-	300	-	Y	AH-1	Type 2 Only
MLT2.7WS (a)	2,2S	50.8	68.6	890	-	300	-	Y	AH-1	Type 2 Only
MLT2H (a)	2,2S	12.7	50.8	2000	-	300	-	Y	AH-1	Type 2 Only
MLT2LH (a)	2,2S	12.7	50.8	1112	-	300	-	Y	AH-1	Type 2 Only
MLT2S (a)	2,2S	12.7	50.8	890	-	300	-	Y	AH-1	Type 2 Only
MLT30S (a)	2,2S	12.7	762	890	-	300	-	Y	AH-1	Type 2 Only
MLT4H (a)	2,2S	12.7	101.6	2000	-	300	-	Y	AH-1	Type 2 Only
MLT4LH (a)	2,2S	12.7	101.6	1112	-	300	-	Y	AH-1	Type 2 Only
MLT4S (a)	2,2S	12.7	101.6	890	-	300	-	Y	AH-1	Type 2 Only
MLT4WH (a)	2,2S	50.8	101.6	2000	-	300	-	Y	AH-1	Type 2 Only
MLT4WLH (a)	2,2S	50.8	101.6	1112	-	300	-	Y	AH-1	Type 2 Only

MLT4WS (a)	2,2S	50.8	101.6	890	-	300	-	Y	AH-1	Type 2 Only
MLT6H (a)	2,2S	12.7	152.4	2000	-	300	-	Y	AH-1	Type 2 Only
MLT6LH (a)	2,2S	12.7	152.4	1112	-	300	-	Y	AH-1	Type 2 Only
MLT6S (a)	2,2S	12.7	152.4	890	-	300	-	Y	AH-1	Type 2 Only
MLT6WH (a)	2,2S	50.8	152.4	2000	-	300	-	Y	AH-1	Type 2 Only
MLT6WLH (a)	2,2S	50.8	152.4	1112	-	300	-	Y	AH-1	Type 2 Only
MLT6WS (a)	2,2S	50.8	152.4	890	-	300	-	Y	AH-1	Type 2 Only
MLT8H (a)	2,2S	12.7	203.2	2000	-	300	-	Y	AH-1	Type 2 Only
MLT8LH (a)	2,2S	12.7	203.2	1112	-	300	-	Y	AH-1	Type 2 Only
MLT8S (a)	2,2S	12.7	203.2	890	-	300	-	Y	AH-1	Type 2 Only
MLT8WH (a)	2,2S	50.8	203.2	2000	-	300	-	Y	AH-1	Type 2 Only
MLT8WLH (a)	2,2S	50.8	203.2	1112	-	300	-	Y	AH-1	Type 2 Only
MLT8WS (a)	2,2S	50.8	203.2	890	-	300	-	Y	AH-1	Type 2 Only
MLTxDEH (a)(c)	2,2S	25.4	1270	3560	-	300	-	Y	AH-1	Type 2 Only
MLTxDEH15 (a)(c)	2,2S	25.4	1270	4450	-	300	-	Y	AH-1	Type 2 Only
MLTxDH (a)(c)	2,2S	12.7	1270	2670	-	300	-	Y	AH-1	Type 2 Only
MLTxDSH (a)(c)	2,2S	25.4	1270	5340	-	300	-	Y	AH-1	Type 2 Only
MLTxEH (a)(c)	2,2S	25.4	1270	2670	-	300	-	Y	AH-1	Type 2 Only
MLTxEH15 (a)(c)	2,2S	25.4	1270	3115	-	300	-	Y	AH-1	Type 2 Only
MLTxSH (a)(c)	2,2S	25.4	1270	4005	-	300	-	Y	AH-1	Type 2 Only

MS10W38T15 (a)	2,2S	25.4	254	2225	-	300	-	Y	AH-1	Type 2 Only
MS10W50T15 (a)	2,2S	25.4	254	3115	-	300	-	Y	AH-1	Type 2 Only
MS10W63T15 (a)	2,2S	25.4	254	3560	-	300	-	Y	AH-1	Type 2 Only
MS10W75T30 (a) (e)	2,2S	25.4	254	10680	-	300	-	Y	AH-1	Type 2 Only
MS12W75T30 (a)(e)	2,2S	25.4	305	10680	-	300	-	Y	AH-1	Type 2 Only
MS14W75T30 (a)(e)	2,2S	25.4	355.6	10680	-	300	-	Y	AH-1	Type 2 Only
MS2W38T15 (a)	2,2S	25.4	50.8	2225	-	300	-	Y	AH-1	Type 2 Only
MS4W38T15 (a)	2,2S	25.4	101.6	2225	-	300	-	Y	AH-1	Type 2 Only
MS4W50T15 (a)	2,2S	25.4	101.6	3115	-	300	-	Y	AH-1	Type 2 Only
MS4W63T15 (a)	2,2S	25.4	101.6	3560	-	300	-	Y	AH-1	Type 2 Only
MS4W75T30 (a)(e)	2,2S	25.4	101.6	10680	-	300	-	Y	AH-1	Type 2 Only
MS6W38T15 (a)	2,2S	25.4	152.4	2225	-	300	-	Y	AH-1	Type 2 Only
MS6W50T15 (a)	2,2S	25.4	152.4	3115	-	300	-	Y	AH-1	Type 2 Only
MS6W63T15 (a)	2,2S	25.4	152.4	3560	-	300	-	Y	AH-1	Type 2 Only
MS6W75T30 (a)(e)	2,2S	25.4	152.4	10680	-	300	-	Y	AH-1	Type 2 Only
MS8W38T15 (a)	2,2S	25.4	203.2	2225	-	300	-	Y	AH-1	Type 2 Only
MS8W50T15 (a)	2,2S	25.4	203.2	3115	-	300	-	Y	AH-1	Type 2 Only
MS8W63T15 (a)	2,2S	25.4	203.2	3560	-	300	-	Y	AH-1	Type 2 Only
MS8W75T30 (a)(e)	2,2S	25.4	203.2	10680	-	300	-	Y	AH-1	Type 2 Only
MSBW38 (a) + MSW38T15 (b) (i)	2,2S	25.4	-	2225	-	300	-	Y	AH-1	Type 2 Only

MSBW50 (a) + MSW50T15 (b) (i)	2,2S	25.4	-	3115	-	300	-	Y	AH-1	Type 2 Only
MSBW63 (a) + MSW63T15 (b) (i)	2,2S	25.4	-	3560	-	300	-	Y	AH-1	Type 2 Only
MSBW75 (a) + MSW75T30 (b)(e) (i)										
	2,2S	25.4	-	10680	-	300	-	Y	AH-1	Type 2 Only
Nonmetallic Cable Ties										
CBR4LH (f)(g)	2,21	8.0	102	534	-60	85	0	-	AH-2	Type 2 Only
CBR4LH-0 (g)	2,21	8.0	102	534	-60	85	0	Y	-	Type 2 Only
CBR4LH-30 thru 39 (g)	2,21	8.0	102	534	-60	115	0	-	-	Type 2 Only
CBR6LH (f)(g)	2,21	8.0	152	534	-60	85	0	-	AH-2	Type 2 Only
CBR6LH-0 (g)	2,21	8.0	152	534	-60	85	0	Y	-	Type 2 Only
CBR6LH-30 thru 39 (g)	2,21	8.0	152	534	-60	115	0	-	-	Type 2 Only
ILT1.5I (f)(g)	2,21	1.6	25	80	-60	85	-20	-	AH-2	Type 2 Only
ILT1.5I-0 (g)	2,21	1.6	25	80	-60	85	-20	Y	-	Type 2 Only
ILT100 (f)(g)	2,21	1.6	25	80	-60	85	-20	-	AH-2	Type 2 Only
ILT150 (f)(g)	2,21	1.6	25	80	-60	85	-20	-	AH-2	Type 2 Only
ILT1M (f)(g)	2,21	1.6	25	80	-60	85	-20	-	AH-2	Type 2 Only
ILT1M-0 (g)	2,21	1.6	25	80	-60	85	-20	Y	-	Type 2 Only
M10-120-* (h)	2,21	4.8	64	534	-40	85	-20	-	AH-2	Type 2 Only
M10-120-*0 (h)	2,21	4.8	64	534	-40	85	-20	Y	AH-2	Type 2 Only
M10-50-* (h)	2,21,2S,21S	3.18	64	222	-40	85	-20	-	AH-2	Type 2 Only
M10-50-*0 (h)	2,21,2S,21S	3.18	64	222	-40	85	-20	Y	AH-2	Type 2 Only

M11-120-* (h)	2,21	4.8	76	534	-40	85	-20	-	AH-2	Type 2 Only
M11-120-*0 (h)	2,21	4.8	76	534	-40	85	-20	Y	AH-2	Type 2 Only
M11-40-* (h)	2,21	1.6	76	178	-40	85	-20	-	AH-2	Type 2 Only
M11-40-*0 (h)	2,21	1.6	76	178	-40	85	-20	Y	AH-2	Type 2 Only
M12-50-* (h)	2,21,2S,21S	3.18	76	222	-40	85	-20	-	AH-2	Type 2 Only
M12-50-*0 (h)	2,21,2S,21S	3.18	76	222	-40	85	-20	Y	AH-2	Type 2 Only
M15-120-* (h)	2,21	4.8	102	534	-40	85	-20	-	AH-2	Type 2 Only
M15-120-*0 (h)	2,21	4.8	102	534	-40	85	-20	Y	AH-2	Type 2 Only
M15-40-* (h)	2,21	1.6	102	178	-40	85	-20	-	AH-2	Type 2 Only
M15-40-*0 (h)	2,21	1.6	102	178	-40	85	-20	Y	AH-2	Type 2 Only
M15-50-* (h)	2,21,2S,21S	3.18	102	222	-40	85	-20	-	AH-2	Type 2 Only
M15-50-*0 (h)	2,21,2S,21S	3.18	102	222	-40	85	-20	Y	AH-2	Type 2 Only
M16-50-* (h)	2,21,2S,21S	3.18	114	222	-40	85	-20	-	AH-2	Type 2 Only
M16-50-*0 (h)	2,21,2S,21S	3.18	114	222	-40	85	-20	Y	AH-2	Type 2 Only
M18-50-* (h)	2,21,2S,21S	3.18	127	222	-40	85	-20	-	AH-2	Type 2 Only
M18-50-*0 (h)	2,21,2S,21S	3.18	127	222	-40	85	-20	Y	AH-2	Type 2 Only
M20-250-* (h)	2,21	12.7	127	1112	-40	85	-20	-	AH-2	Type 2 Only
M22-120-* (h)	2,21	4.8	152	534	-40	85	-20	-	AH-2	Type 2 Only
M22-120-*0 (h)	2,21	4.8	152	534	-40	85	-20	Y	AH-2	Type 2 Only
M22-250-* (h)	2,21	12.7	152	1112	-40	85	-20	-	AH-2	Type 2 Only

M25-120-* (h)	2,21	4.8	178	534	-40	85	-20	-	AH-2	Type 2 Only
M25-120-*0 (h)	2,21	4.8	178	534	-40	85	-20	Y	AH-2	Type 2 Only
M28-120-* (h)	2,21	4.8	203	534	-40	85	-20	-	AH-2	Type 2 Only
M28-120-*0 (h)	2,21	4.8	203	534	-40	85	-20	Y	AH-2	Type 2 Only
M28-250-* (h)	2,21	63.5	203	1112	-40	85	-20	-	AH-2	Type 2 Only
M31-120-* (h)	2,21	4.8	229	534	-40	85	-20	-	AH-2	Type 2 Only
M31-120-*0 (h)	2,21	4.8	229	534	-40	85	-20	Y	AH-2	Type 2 Only
M34-120-* (h)	2,21	4.8	262	534	-40	85	-20	-	AH-2	Type 2 Only
M34-250-* (h)	2,21	63.5	254	1112	-40	85	-20	-	AH-2	Type 2 Only
M4-18-* (h)	2,21	1.6	22	80	-40	85	-20	-	AH-2	Type 2 Only
M4-18-*0 (h)	2,21	1.6	22	80	-40	85	-20	Y	AH-2	Type 2 Only
M40-250-* (h)	2,21	63.5	305	1112	-40	85	-20	-	AH-2	Type 2 Only
M5-50-* (h)	2,21,2S,21S	3.18	25	222	-40	85	-20	-	AH-2	Type 2 Only
M5-50-*0 (h)	2,21,2S,21S	3.18	25	222	-40	85	-20	Y	AH-2	Type 2 Only
M6-18-* (h)	2,21	1.6	32	80	-40	85	-20	-	AH-2	Type 2 Only
M6-18-*0 (h)	2,21	1.6	32	80	-40	85	-20	Y	AH-2	Type 2 Only
M6-40-* (h)	2,21	1.6	35	178	-40	85	-20	-	AH-2	Type 2 Only
M6-40-*0 (h)	2,21	1.6	35	178	-40	85	-20	Y	AH-2	Type 2 Only
M6-50-* (h)	2,21,2S,21S	3.18	38	222	-40	85	-20	-	AH-2	Type 2 Only
M6-50-*0 (h)	2,21,2S,21S	3.18	38	222	-40	85	-20	Y	AH-2	Type 2 Only

M7-50-* (h)	2,21,2S,21S	3.18	48	222	-40	85	-20	-	AH-2	Type 2 Only
M7-50-*0 (h)	2,21,2S,21S	3.18	48	222	-40	85	-20	Y	AH-2	Type 2 Only
M8-120-* (h)	2,21	4.8	51	534	-40	85	-20	-	AH-2	Type 2 Only
M8-120-*0 (h)	2,21	4.8	51	534	-40	85	-20	Y	AH-2	Type 2 Only
M8-18-* (h)	2,21	1.6	51	80	-40	85	-20	-	AH-2	Type 2 Only
M8-18-*0 (h)	2,21	1.6	51	80	-40	85	-20	Y	AH-2	Type 2 Only
M8-40-* (h)	2,21	1.6	51	178	-40	85	-20	-	AH-2	Type 2 Only
M8-40-*0 (h)	2,21	1.6	51	178	-40	85	-20	Y	AH-2	Type 2 Only
M9-250-* (h)	2,21	12.7	51	1112	-40	85	-20	-	AH-2	Type 2 Only
MR7-50-* (h)	2,21,2S,21S	3.18	48	222	-40	85	-20	-	AH-2	Type 2 Only
MR7-50-*0 (h)	2,21,2S,21S	3.18	48	222	-40	85	-20	Y	AH-2	Type 2 Only
PLT.7M-0 (g)	2,21	1.6	17	80	-60	85	0	Y	AH-2	Type 2 Only
PLT.7M-00 (g)	2,21	1.6	17	80	-60	85	0	Y	-	Type 2 Only
PLT.7M-30 thru 39 (g)	2,21	1.6	17	80	-60	115	0	-	-	Type 2 Only
PLT1.5I-6120 (g)	2,21	1.5	35	111	-60	65	-20	Y	AH-2	Type 2 Only
PLT1.5IG (f)(g)	2,21	1.6	35	178	-60	85	-20	-	AH-1	Type 2 Only
PLT1.5IG-0 (g)	2,21	1.6	35	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT1.5M-XMR (f)(g)	2,21	0.5	33	80	-60	85	-20	-	AH-2	Type 2 Only
PLT1.5M-XMR0 (g)	2,21	0.5	33	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT1.5M-XMR00 (g)	2,21	0.5	33	80	-60	85	-20	Y	-	Type 2 Only

PLT1.5M-XMR30 thru 39 (g)	2,21	0.5	33	80	-60	115	-20	-	-	Type 2 Only
PLT1.5S (f)(g)	2,21,2S,21S	1.6	38	222	-60	85	0	-	AH-2	Type 2 Only
PLT1.5S-0 (g)	2,21,2S,21S	1.6	38	222	-60	85	0	Y	AH-2	Type 2 Only
PLT1.5S-00 (g)	2,21	1.6	38	222	-60	85	0	Y	-	Type 2 Only
PLT1.5S-30 thru 39 (g)	2,21	1.6	38	222	-60	115	0	-	-	Type 2 Only
PLT1.5S-300 (g)	2	1.6	38	222	-60	115	0	Y	AH-2	Type 2 Only
PLT1.5S-300 (g)	2	3.18	38	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT100M (f)(g)	2,21	0.8	23	80	-60	85	-20	-	AH-2	Type 2 Only
PLT100M-0 (g)	2,21	0.8	23	80	-60	85	-20	Y	-	Type 2 Only
PLT100MG (f)(g)	2,21	0.8	23	80	-60	85	-20	-	AH-2	Type 2 Only
PLT100MG-0 (g)	2,21	0.8	23	80	-60	85	-20	Y	-	Type 2 Only
PLT1M-XMR (f)(g)	2,21	0.5	21	80	-60	85	-20	-	AH-2	Type 2 Only
PLT1M-XMR0 (g)	2,21	0.5	21	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT1M-XMR00 (g)	2,21	0.5	21	80	-60	85	-20	Y	-	Type 2 Only
PLT1M-XMR30 thru 39 (g)	2,21	0.5	21	80	-60	115	-20	-	-	Type 2 Only
PLT1M-XMR300 (g)	2	0.5	21	80	-60	115	-20	Y	AH-2	Type 2 Only
PLT1MG (f)(g)	2,21	1.6	22	80	-60	85	-20	-	AH-2	Type 2 Only
PLT1MG-0 (g)	2,21	1.6	22	80	-60	85	-20	Y	AH-2	Type 2 Only
PLT1S (f)(g)	2,21,2S,21S	1.6	25	222	-60	85	0	-	AH-2	Type 2 Only
PLT1S-0 (g)	2,21,2S,21S	1.6	25	222	-60	85	0	Y	AH-2	Type 2 Only

PLT1S-00 (g)	2,21	1.6	25	222	-60	85	0	Y	-	Type 2 Only
PLT1S-30 thru 39 (g)	2,21	1.6	25	222	-60	115	0	-	-	Type 2 Only
PLT1S-300 (g)	2	1.6	25	222	-60	115	0	Y	AH-2	Type 2 Only
PLT2.5S (f)(g)	2,21,2S,21S	1.6	64	222	-60	85	0	-	AH-2	Type 2 Only
PLT2.5S-0 (g)	2,21,2S,21S	1.6	64	222	-60	85	0	Y	AH-2	Type 2 Only
PLT2.5S-00 (g)	2,21	1.6	64	222	-60	85	0	Y	-	Type 2 Only
PLT2.5S-30 thru 39 (g)	2,21	1.6	64	222	-60	115	0	-	-	Type 2 Only
PLT2.5S-30 thru 39 (g)	2,21	1.6	64	222	-60	115	-20	-	-	Type 2 Only
PLT2.5S-300 (g)	2	1.6	64	222	-60	115	0	Y	AH-2	Type 2 Only
PLT2.5S-6120 (g)	2,21	1.5	63.5	222	-60	65	-20	Y	AH-2	Type 2 Only
PLT2IG (f)(g)	2,21	1.6	51	178	-60	85	-20	-	AH-2	Type 2 Only
PLT2IG-0 (g)	2,21	1.6	51	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT2MG (f)(g)	2,21	1.6	51	178	-60	85	-20	-	AH-2	Type 2 Only
PLT2MG-0 (g)	2,21	1.6	51	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT2S (f)(g)	2,21,2S,21S	1.6	48	222	-60	85	0	-	AH-2	Type 2 Only
PLT2S-0 (g)	2,21,2S,21S	1.6	48	222	-60	85	0	Y	AH-2	Type 2 Only
PLT2S-00 (g)	2,21	1.6	48	222	-60	85	0	Y	-	Type 2 Only
PLT2S-30 thru 39 (g)	2,21	1.6	48	222	-60	115	0	-	-	Type 2 Only
PLT2S-300 (g)	2	1.6	48	222	-60	115	0	Y	AH-2	Type 2 Only
PLT2S-6120 (g)	2,21	1.5	48	222	-60	65	-20	Y	AH-2	Type 2 Only

PLT2S-VMR (f)(g)	2,21,2S,21S	1.6	49	222	-60	85	0	-	AH-2	Type 2 Only
PLT2S-VMR (f)(g)	2,21,2S,21S	3.18	49	222	-60	85	-20	-	AH-2	Type 2 Only
PLT2S-VMR0 (g)	2,21,2S,21S	1.6	49	222	-60	85	0	Y	AH-2	Type 2 Only
PLT2S-VMR0 (g)	2,21,2S,21S	3.18	49	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT2S-VMR00 (g)	2,21	1.6	49	222	-60	85	0	Y	-	Type 2 Only
PLT2S-VMR00 (g)	2,21	3.18	49	222	-60	85	-20	Y	-	Type 2 Only
PLT2S-VMR30 thru 39 (g)	2,21	3.18	49	222	-60	115	-20	-	-	Type 2 Only
PLT2S-VMR30 thru 39 (g)	2,21	1.6	49	222	-60	115	0	-	-	Type 2 Only
PLT2S-VMR300 (g)	2	1.6	49	222	-60	115	0	Y	AH-2	Type 2 Only
PLT2S-VMR300 (g)	2	3.18	3.18	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT2SG (f)(g)	2,21,2S,21S	1.6	48	222	-60	85	0	-	AH-2	Type 2 Only
PLT2SG (f)(g)	2,21,2S,21S	3.18	48	222	-60	85	-20	-	AH-2	Type 2 Only
PLT2SG-0 (g)	2,21,2S,21S	3.18	48	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT2SG-0 (g)	2,21,2S,21S	1.6	48	222	-60	85	0	Y	AH-2	Type 2 Only
PLT3IG (f)(g)	2,21	1.6	76	178	-60	85	-20	-	AH-2	Type 2 Only
PLT3IG-0 (g)	2,21	1.6	76	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT3S (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	0	-	AH-2	Type 2 Only
PLT3S-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	0	Y	AH-2	Type 2 Only
PLT3S-00 (g)	2,21	1.6	76	222	-60	85	0	Y	-	Type 2 Only
PLT3S-30 thru 39 (g)	2,21	1.6	76	222	-60	115	0	-	-	Type 2 Only

PLT3S-300 (g)	2	1.6	76	222	-60	115	0	Y	AH-2	Type 2 Only
PLT3S-6120 (g)	2,21	1.5	76	222	-60	65	-20	Y	AH-2	Type 2 Only
PLT3S-VMR (f)(g)	2,21,2S,21S	3.18	70	222	-60	85	-20	-	AH-2	Type 2 Only
PLT3S-VMR (f)(g)	2,21,2S,21S	1.6	70	222	-60	85	0	-	AH-2	Type 2 Only
PLT3S-VMR0 (g)	2,21,2S,21S	1.6	70	222	-60	85	0	Y	AH-2	Type 2 Only
PLT3S-VMR0 (g)	2,21,2S,21S	3.18	70	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT3S-VMR00 (g)	2,21	3.18	70	222	-60	85	-20	Y	-	Type 2 Only
PLT3S-VMR00 (g)	2,21	1.6	70	222	-60	85	0	Y	-	Type 2 Only
PLT3S-VMR30 thru 39 (g)	2,21	1.6	70	222	-60	115	0	-	-	Type 2 Only
PLT3S-VMR30 thru 39 (g)	2,21	3.18	70	222	-60	115	-20	-	-	Type 2 Only
PLT3S-VMR300 (g)	2	3.18	70	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT3S-VMR300 (g)	2	1.6	70	222	-60	115	0	Y	AH-2	Type 2 Only
PLT3SG (f)(g)	2,21,2S,21S	3.18	76	222	-60	85	-20	-	AH-2	Type 2 Only
PLT3SG (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	0	-	AH-2	Type 2 Only
PLT3SG-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	0	Y	AH-2	Type 2 Only
PLT3SG-0 (g)	2,21,2S,21S	3.18	76	222	-60	85	-20	Y	AH-2	Type 2 Only
PLT4.5S (f)(g)	2,21,2S,21S	1.6	114	222	-60	85	0	-	AH-2	Type 2 Only
PLT4.5S-0 (g)	2,21,2S,21S	1.6	114	222	-60	85	0	Y	AH-2	Type 2 Only
PLT4.5S-00 (g)	2,21	1.6	114	222	-60	85	0	Y	-	Type 2 Only
PLT4.5S-30 thru 39 (g)	2,21	1.6	114	222	-60	115	0	-	-	Type 2 Only

PLT4.5S-300 (g)	2	1.6	114	222	-60	115	0	Y	AH-2	Type 2 Only
PLT4H-6120 (g)	2,21	1.5	102	534	-60	65	-20	Y	AH-2	Type 2 Only
PLT4IG (f)(g)	2,21	1.6	102	178	-60	85	-20	-	AH-2	Type 2 Only
PLT4IG-0 (g)	2,21	1.6	102	178	-60	85	-20	Y	AH-2	Type 2 Only
PLT4S (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	0	-	AH-2	Type 2 Only
PLT4S-0 (g)	2,21,2S,21S	1.6	102	222	-60	85	0	Y	AH-2	Type 2 Only
PLT4S-00 (g)	2,21	1.6	102	222	-60	85	0	Y	-	Type 2 Only
PLT4S-30 thru 39 (g)	2,21	1.6	102	222	-60	115	0	-	-	Type 2 Only
PLT4S-300 (g)	2	1.6	102	222	-60	115	0	Y	AH-2	Type 2 Only
PLT4S-6120 (g)	2,21	1.5	102	222	-60	65	-20	Y	AH-2	Type 2 Only
PLT4SG (f)(g)	2,21,2S,21S	1.6	102	222	-60	115	0	-	AH-2	Type 2 Only
PLT4SG (f)(g)	2,21,2S,21S	3.18	102	222	-60	115	-20	-	AH-2	Type 2 Only
PLT4SG-0 (g)	2,21	1.6	102	222	-60	115	0	Y	AH-2	Type 2 Only
PLT4SG-0 (g)	2,21	3.18	102	222	-60	115	-20	Y	AH-2	Type 2 Only
PLT5S (f)(g)	2,21,2S,21S	1.6	127	222	-60	85	0	-	AH-2	Type 2 Only
PLT5S-0 (g)	2,21,2S,21S	1.6	127	222	-60	85	0	Y	AH-2	Type 2 Only
PLT5S-00 (g)	2,21	1.6	127	222	-60	85	0	Y	-	Type 2 Only
PLT5S-30 thru 39 (g)	2,21	1.6	127	222	-60	115	0	-	-	Type 2 Only
PLT5S-300 (g)	2	1.6	127	222	-60	115	0	Y	AH-2	Type 2 Only
PLT7LH-6120 (g)	2,21	1.5	178	534	-60	65	-20	Y	AH-2	Type 2 Only

PLT80 (f)(g)	2,21	1.6	17	80	-60	85	0	-	AH-2	Type 2 Only
PLT80B (g)	2,21	1.6	17	80	-60	85	0	Y	AH-2	Type 2 Only
PLT8LH-6120 (g)	2,21	1.5	203	534	-60	65	-20	Y	AH-2	Type 2 Only
PRT1.5S (f)(g)	2,21,2S,21S	1.6	38	222	-60	85	0	-	AH-2	Type 2 Only
PRT1.5S-0 (g)	2,21,2S,21S	1.6	38	222	-60	85	0	Y	AH-2	Type 2 Only
PRT1.5S-00 (g)	2,21	1.6	38	222	-60	85	0	Y	-	Type 2 Only
PRT1.5S-30 thru 39 (g)	2,21	1.6	38	222	-60	115	0	-	-	Type 2 Only
PRT1.5S-300 (g)	2	1.6	38	222	-60	115	0	Y	AH-2	Type 2 Only
PRT1S (f)(g)	2,21,2S,21S	1.6	25	222	-60	85	0	-	AH-2	Type 2 Only
PRT1S-0 (g)	2,21,2S,21S	1.6	25	222	-60	85	0	Y	AH-2	Type 2 Only
PRT1S-00 (g)	2,21	1.6	25	222	-60	85	0	Y	-	Type 2 Only
PRT1S-30 thru 39 (g)	2,21	1.6	25	222	-60	115	0	-	-	Type 2 Only
PRT1S-300 (g)	2	1.6	25	222	-60	115	0	Y	AH-2	Type 2 Only
PRT2S (f)(g)	2,21,2S,21S	1.6	48	222	-60	85	0	-	AH-2	Type 2 Only
PRT2S-0 (g)	2,21,2S,21S	1.6	48	222	-60	85	0	Y	AH-2	Type 2 Only
PRT2S-00 (g)	2,21	1.6	48	222	-60	85	0	Y	-	Type 2 Only
PRT2S-30 thru 39 (g)	2,21	1.6	48	222	-60	115	0	-	-	Type 2 Only
PRT2S-300 (g)	2	1.6	48	222	-60	115	0	Y	AH-2	Type 2 Only
PRT3S (f)(g)	2,21,2S,21S	1.6	76	222	-60	85	0	-	AH-2	Type 2 Only
PRT3S-0 (g)	2,21,2S,21S	1.6	76	222	-60	85	0	Y	AH-2	Type 2 Only

PRT3S-00 (g)	2,21	1.6	76	222	-60	85	0	Y	-	Type 2 Only
PRT3S-30 thru 39 (g)	2,21	1.6	76	222	-60	115	0	-	-	Type 2 Only
PRT3S-300 (g)	2	1.6	76	222	-60	115	0	Y	AH-2	Type 2 Only
PRT4S (f)(g)	2,21,2S,21S	1.6	102	222	-60	85	0	-	AH-2	Type 2 Only
PRT4S-0 (g)	2,21,2S,21S	1.6	102	222	-60	85	0	Y	AH-2	Type 2 Only
PRT4S-00 (g)	2,21	1.6	102	222	-60	85	0	Y	-	Type 2 Only
PRT4S-30 thru 39 (g)	2,21	1.6	102	222	-60	115	0	-	-	Type 2 Only
PRT4S-300 (g)	2	1.6	102	222	-60	115	0	Y	AH-2	Type 2 Only
Nonmetallic Cable Ties - Nylon										
S10-50-%	2,21	3	60	222	-40	85	-20	-	AH-2	-
S10-50-%0	2,21	3	60	222	-40	85	-20	Y	AH-2	-
S12-40-%	2,21	2	76	178	-40	85	-20	-	AH-2	-
S12-40-%0	2,21	2	76	178	-40	85	-20	Y	AH-2	-
S12-50-%	2,21	3	76	222	-40	85	-20	-	AH-2	-
S12-50-%0	2,21	3	76	222	-40	85	-20	Y	AH-2	-
S14-120-%	2,21	7	102	534	-40	85	-20	-	AH-2	-
S14-120-%0	2,21	7	102	534	-40	85	-20	Y	AH-2	-
S15-40-%	2,21	2	102	178	-40	85	-20	-	AH-2	-
S15-40-%0	2,21	2	102	178	-40	85	-20	Y	AH-2	-
S15-50-%	2,21	3	102	222	-40	85	-20	-	AH-2	-
S15-50-%0	2,21	3	102	222	-40	85	-20	Y	AH-2	-
S17-50-%	2,21	3	110	222	-40	85	-20	-	AH-2	-
S17-50-%0	2,21	3	110	222	-40	85	0	Y	AH-2	-
S18-120-%	2,21	7	130	534	-40	85	-20	-	AH-2	-
S18-120-%0	2,21	7	130	534	-40	85	-20	Y	AH-2	-
S18-175-%	2,21	7	132	778	-40	85	-20	-	AH-2	-
S18-175-%0	2,21	7	132	778	-40	85	-20	Y	AH-2	-

S21-120-%	2,21	7	140	534	-40	85	-20	-	AH-2	-
S21-120-%0	2,21	7	140	534	-40	85	-20	Y	AH-2	-
S21-175-%	2,21	7	140	778	-40	85	-20	-	AH-2	-
S21-175-%0	2,21	7	140	778	-40	85	-20	Y	AH-2	-
S21-50-%	2,21	3	140	222	-40	85	-20	-	AH-2	-
S21-50-%0	2,21	3	140	222	-40	85	0	Y	AH-2	-
S24-120-%	2,21	7	175	534	-40	85	-20	-	AH-2	-
S24-120-%0	2,21	7	175	534	-40	85	-20	Y	AH-2	-
S24-175-%	2,21	7	187	778	-40	85	-20	-	AH-2	-
S24-175-%0	2,21	7	187	778	-40	85	-20	Y	AH-2	-
S30-120-%	2,21	7	218	534	-40	85	-20	-	AH-2	-
S30-120-%0	2,21	7	218	534	-40	85	-20	Y	AH-2	-
S31-175-%	2,21	7	228	778	-40	85	-20	-	AH-2	-
S31-175-%0	2,21	7	228	778	-40	85	-20	Y	AH-2	-
S32-175-%	2,21	7	239	778	-40	85	-20	-	AH-2	-
S32-175-%0	2,21	7	239	778	-40	85	-20	Y	AH-2	-
S36-175-%	2,21	7	263	778	-40	85	-20	-	AH-2	-
S36-175-%0	2,21	7	263	778	-40	85	-20	Y	AH-2	-
S4-18-%	2,21	1.5	22	80	-40	85	-20	-	AH-2	-
S4-18-%0	2,21	1.5	22	80	-40	85	-20	Y	AH-2	-
S40-175-%	2,21	7	295	778	-40	85	-20	-	AH-2	-
S40-175-%0	2,21	7	295	778	-40	85	-20	Y	AH-2	-
S48-175-%	2,21	7	365	778	-40	85	-20	-	AH-2	-
S48-175-%0	2,21	7	365	778	-40	85	-20	Y	AH-2	-
S5-50-%	2,21	3	24	222	-40	85	-20	-	AH-2	-
S5-50-%0	2,21	3	24	222	-40	85	-20	Y	AH-2	-
S6-18-%	2,21	1.5	40	80	-40	85	-20	-	AH-2	-
S6-18-%0	2,21	1.5	40	80	-40	85	-20	Y	AH-2	-
S6-40-%	2,21	2	33	178	-40	85	0	-	AH-2	-
S6-40-%0	2,21	2	33	178	-40	85	0	Y	AH-2	-
S6-50-%	2,21	3	38	222	-40	85	-20	-	AH-2	-

S6-50-%0	2,21	3	38	222	-40	85	-20	Y	AH-2	-
S7-50-%	2,21	3	46	222	-40	85	-20	-	AH-2	-
S7-50-%0	2,21	3	46	222	-40	85	-20	Y	AH-2	-
S8-18-%	2,21	1.5	53	80	-40	85	-20	-	AH-2	-
S8-18-%0	2,21	1.5	53	80	-40	85	-20	Y	AH-2	-
S8-40-%	2,21	2	53	178	-40	85	0	-	AH-2	-
S8-40-%0	2,21	2	53	178	-40	85	0	Y	AH-2	-
S8-50-%	2,21	3	53	222	-40	85	-20	-	AH-2	-
S8-50-%0	2,21	3	53	222	-40	85	-20	Y	AH-2	-
SR8-50-%	2,21	3	50	222	-40	85	-20	-	AH-2	-
SR8-50-%0	2,21	3	50	222	-40	85	-20	Y	AH-2	-

Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type	Mechanical		Hole Dia.	Panel	Operating		Resistant	Air	IEC 62275
		Str. N	mm	mm	Temp.	to	Handling	Spaces	Type	
Metallic Fixing Devices										
UCFG1 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only
UCIB1 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only
UCRND1 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only
UCSQ1 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only
UCTH1 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only
UCUC2 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only
UCUC3 (a)	2,2S	890	-	-	-	-60	300	Y	AH-1	Type 2 Only

Integral Assemblies Investigated to ANSI/UL 62275

Cat. No.	Type	Bundle Dia. mm	Loop Tensile Str. N	Mechanical Str. N	Hole Dia. mm	Panel Thick. mm	Operating Temp. °C	Min.	Resistant to UV Light	Air Handling Spaces	IEC 62275 Type
								Install. Temp. °C			

		Min	Max			Min	Max								
Composite Cable Ties with Integral Screw Mount Fixing Device															
BC1.5M-S4 (f)(g)	2,21	1.6	38	80	44	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC1M-S4 (f)(g)	2,21	1.6	23	80	44	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC2M-S4 (f)(g)	2,21	1.6	51	80	44	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC2S-S10 (f) (g)	2,21	1.6	51	222	133	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC2SG-S10 (f) (g)	2,21	1.6	51	222	133	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC3S-S10 (f) (g)	2,21	1.6	76	222	133	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC4LH-S25 (f) (g)	2,21	4.8	102	534	356	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC4LHG-S25 (f) (g)	2,21	4.8	102	534	356	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC4S-S10 (f) (g)	2,21	1.6	102	222	133	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
BC4SG-S10 (f) (g)	2,21	1.6	102	222	133	-	-	-	-60	85	-20	-	AH-2	Type 2 Only	
Nonmetallic Cable Ties with Integral Fixing Device															
SC15-120-S25-%	2,21	7	98	534	534	-	-	-	-40	85	-20	-	AH-2	-	
SC15-120-S25-%0	2,21	7	98	534	534	-	-	-	-40	85	-20	Y	AH-2	-	
Nonmetallic Cable Ties with Integral Screw Mount Fixing Devices															
MC15-120-S25-*(h)	2,21	12.7	102	534	267	-	-	-	-40	85	-20	-	AH-2	Type 2 Only	

MC8-50-S10-*(h)	2,21	3.18	47	222	89	-	-	-	-40	85	-20	-	AH-2	Type 2 Only
PLC1.5I-S8 (f)(g)	2,21	1.6	32	178	67	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC1M-S4 (f)(g)	2,21	1.6	19	80	44	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC2H-S25 (f)(g)	2,21	4.8	51	534	267	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC2S-S10 (f)(g)	2,21	1.6	47	222	89	-	-	-	-60	85	0	-	AH-2	Type 2 Only
PLC2S-S10 (f)(g)	2,21	3.18	47	222	89	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC2S-S6 (f)(g)	2,21	3.18	47	222	89	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC2S-S6 (f)(g)	2,21	1.6	47	222	89	-	-	-	-60	85	0	-	AH-2	Type 2 Only
PLC3S-S10 (f)(g)	2,21	1.6	76	222	89	-	-	-	-60	85	0	-	AH-2	Type 2 Only
PLC3S-S10 (f)(g)	2,21	3.18	76	222	89	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC4H-S25 (f)(g)	2,21	4.8	102	534	267	-	-	-	-60	85	-20	-	AH-2	Type 2 Only
PLC4S-S10 (f)(g)	2,21	1.6	102	222	89	-	-	-	-60	85	0	-	AH-2	Type 2 Only
PLC4S-S10 (f)(g)	2,21	3.18	102	222	89	-	-	-	-60	85	-20	-	AH-2	Type 2 Only

% - may be followed by X, Q, L, C, T, TL, D, or M; may be followed by 2 or 8.

(a) - Suffix consisting of a dash (-) followed by one or two letters, followed by a package quantity code, followed by material designation, and may be followed by G or GM.

(b) - Suffix consisting of a dash (-) followed by one or two letters package quantity code, followed by an R (Reel/Roll), followed by a material designation.

- (c) - For MLT models, where x denotes 1 thru 50.
- (d) - For IMLT models, where x denotes 25 thru 1270.
- (e) - For loop tensile strength, single loop is 10675 N (2400 lbf), reference individual report for double loop.
- (f) - Leave blank for natural, 1 thru 10, 12, 14, 15, 16, 16A, 18A, 20, 53, 54, 55, 55B, 59, Y, UV2, UV2A, UV4Y, UV5A, UV5B, UV6, UV6A, UV6B, UV7A, UV8, UV8A, UV10, UV11, UV14, UV15, UV16B, UV18. OR UV315
- (g) - Pack codes: 4KR, 5K, 50K, C, CJ, D, DTP, L, M, MJ, MP, Q, T, TL, V or X; may be followed by G, GM, /B, /CK, /CL, /D, /E, /G, /KS, /N, /NL or /R; may be followed by /1 thru /999.
- (h) - Suffix may be followed by /1 thru /999.
- (i) - Cat nos. separated by $\zeta + \zeta$ indicate buckle/strapping combinations. Value of maximum bundle diameter is based on overall length
- * - May be followed by X, Q, L, C, T, TL, D or M.

Note - For Nonmetallic Cable Ties, Several Cat. Nos. may be combined in a single packaged kit. The kit designated KB-550 contains Cat. Nos. PLT1M-M, PLT1M-M0, PLT1.5I-M, PLT1.5I-M0, PLT2S-M, PLT2S-M0, PLT3S-M and PLT3S-M0. The kit designated KB-551 contains Cat. Nos. BT1M-M, BT1M-M0, BT1.5I-M, BT1.5I-M0, BT2S-M, BT2S-M0, BT3S-M and BT3S-M0.

Trademark and/or Tradename: "E56854", "P", "Panduit"

Last Updated on 2024-06-05

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."